



**AUDIO JACKS: STX-35332 Series**  
Surface Mount 3.5mm Audio Jack

**Product Features**

Offered in a 3-Pole Version  
Used in Devices Such as Audio Equipment, Cell Phones,  
or Digital Still Camera  
Complies with EIA Standards  
CSA/NRTL Certified File No. LR78160

**Performance Specifications**

**Materials and Finish**

**Housing**  
High Temperature Thermoplastic, UL 94V-0 Rated

**Terminals**

Copper Alloy, Gold Plated

**Electrical Characteristics**

**Contact Resistance**  
**Before Durability Test**

50 milliohms Max.

**After Durability Test**

100 milliohms Max.

**Insulation Resistance**

100 Megohms Min. at 500V DC

**Dielectric Withstanding Voltage**

500V AC RMS for 1 Minute

**Operating Temperature**

-25°C to + 70°C


Generated Part Number

**STX-35332-3N-TR**

Part Number Builder

STX-35332	-	3	N	TR
Series		Number of Pins	Threading Option	Packaging

**Series**

STX-35332 - Surface Mount 3.5mm Audio Jack

**Number of Pins**

3 - Pins

4 - Pins

5 - Pins

**Threading Option**

N - Non-Threaded Barrel

**Packaging**

TR - Tape and Reel

Contact Kycon for other options

**STX-35332**

Dimensions in mm

**STX-35332-3N-TR**

