

# POEB3FW

## Power over ethernet (PoE)/PD forward transformer



### Product features

- Forward topology
- IEEE 802.3xx
- 1500 Vac isolation between primary and secondary
- EFD25 SMT package (32.8 mm x 26.8 mm x 14.8 mm)
- Power level: 50 watts
- Low leakage inductance
- Ferrite core material
- Moisture sensitivity level (MSL): 1

### Applications

- Lighting
- Industrial automation
- Security systems
- VoIP phone systems
- Network and Bluetooth access points
- Network routers, repeaters
- Uninterruptible power supplies (UPS)
- Retail point-of-information (POI) systems
- Vending and gaming machines
- Remote cameras

### Environmental compliance and general specifications

- Storage temperature (component): -40 °C to +125 °C
- Operating temperature range: -40 °C to +125 °C (ambient plus self-temperature rise)




*Powering Business Worldwide*

**Product specifications**


| Part number <sup>3</sup> | Output power (W) | OCL <sup>1</sup> (µH) ±40% | SCL <sup>2</sup> (µH) maximum | Turns Ratio<br>Schematic 1: Pri : Sec<br>1 : Aux<br>±3% | Output               | DCR (mΩ) maximum @ +25 °C (Pri) | DCR (mΩ) maximum @ +25 °C (Sec 1) | DCR (mΩ) maximum @ +25 °C (Aux) | Schematic |
|--------------------------|------------------|----------------------------|-------------------------------|---|----------------------|---------------------------------|-----------------------------------|---------------------------------|-----------|
| POEB3FW1V50W1X5          | 50               | 162                        | 0.3                           | 1:0.222:0.556   | (1) x 5.0 V @ 10.0 A | 30                              | 5                                 | 60                              | 1         |

- Open circuit inductance (OCL) is for the primary, test parameters: 100 kHz, 0.1 V<sub>rms</sub>, 0.0 Adc, +25 °C
- Short circuit inductance (SCL) is for the primary with the other windings shorted, test parameters: 100 kHz, 0.1 V<sub>rms</sub>, 0.0 Adc, +25 °C
- Part Number Definition: POEB3FWxVxWxXx  
POEB3FW=Product code and size  
xVxW, xV=Version indicator, xW= Output power, xXx=number of outputs and output voltage

**Mechanical parameters, schematic, pad layout (mm)**




**Recommended PCB Layout**



| Dimension | Value        |
|-----------|--------------|
| A         | 26.8 maximum |
| B         | 32.8 maximum |
| C         | 14.8 maximum |
| D         | 29.5 typical |
| E         | 4.0 ± 0.3    |
| G         | 1.1 ± 0.2    |


**Schematic**



Part marking: Dot indicates pin 1, POEB3FW = Product code and size, xV=Version indicator, xW= Output power, xXx=number of outputs and output voltage, wwlyy R= Lot code  
All pin length doesn't include tin icicles  
All soldering surfaces to be coplanar within 0.13 millimeters  
Tolerances are ±0.25 millimeters unless stated otherwise  
Pad layout tolerances are ±0.1 millimeters unless stated otherwise  
Traces or vias underneath the transformer is not recommended

**Packaging information (mm)**

Supplied in tape and reel packaging, 13" diameter reel (EIA-481 compliant)  
 100 parts per reel



| Dimension      | Value |
|----------------|-------|
| $W \pm 0.30$   | 56    |
| $F \pm 0.10$   | 26.2  |
| $E1 \pm 0.10$  | 1.75  |
| $P0 \pm 0.10$  | 4     |
| $P1 \pm 0.10$  | 36    |
| $P2 \pm 0.15$  | 2     |
| $D0 + 0.10/-0$ | 1.5   |
| $D1$ minimum   | 2     |
| $A0 \pm 0.10$  | 28    |
| $A1$ ref.      | 25.4  |
| $B0 \pm 0.10$  | 33.6  |
| $B1 \pm 0.1$   | 26.4  |
| $K0 \pm 0.10$  | 14.8  |
| $T \pm 0.05$   | 0.5   |
| $T1$ maximum   | 0.1   |
| $T2$ maximum   | 15.5  |
| $S0$           | 52.4  |

## General specifications

---

Reflow: MIL-STD-202G Condition J, +245 °C ± 5 °C, 30 s ± 5 s, 1 times reflow

---

Solderability: J-STD-002. 8 hours steam age test, Flux type: ROL0, Solder: +245 °C ± 5 °C

---

Mechanical shock: MIL-STD-202 Method 213. Half-sine shock pulse, peak=100 g's, 6.0 ms, total 18 shocks

---

Vibration: MIL-STD-202, Method 204. Gravity= 10 g, Frequency= 10 Hz to 55 Hz to 10 Hz, Direction: 3 ( X,Y, Z), each 12 cycles, Duration= 20 minutes in each direction

---

Salt spray: GB/T6461-2002, Salt spray concentration= 5% ± 1%, Test temperature= +35 ± 2 °C, pH value= 6.5 to 7.2, Time= 48 hours, After removing the product, wash in warm water or salted water, then natural air-dried for 1 hour

---

High temperature storage test: MIL-STD-202G Method 108, +125 °C, Duration= 1000 hours

---

Temperature cycling: JESD22 Method JA-104, High temperature= +125 °C, low temperature -40 °C, conversion time 30 minutes, 100 cycles.

---

Biased humidity: MIL-STD-202G Method 103, +85 °C, 85% RH, Duration= 1000 hours.

---

Life: MIL-STD-202 Method 108, 1000 hours, +85 °C at rated  $I_{rms}$  (Ambient plus self temperature rise no more than +125 °C)

---

Solder reflow profile




Table 1 - Standard SnPb solder ( $T_C$ )

| Package Thickness | Volume mm <sup>3</sup> <350 | Volume mm <sup>3</sup> ≥350 |
|-------------------|-----------------------------|-----------------------------|
| <2.5 mm           | 235 °C                      | 220 °C                      |
| ≥2.5 mm           | 220 °C                      | 220 °C                      |

Table 2 - Lead (Pb) free solder ( $T_C$ )

| Package thickness | Volume mm <sup>3</sup> <350 | Volume mm <sup>3</sup> 350 - 2000 | Volume mm <sup>3</sup> >2000 |
|-------------------|-----------------------------|-----------------------------------|------------------------------|
| <1.6 mm           | 260 °C                      | 260 °C                            | 260 °C                       |
| 1.6 – 2.5 mm      | 260 °C                      | 250 °C                            | 245 °C                       |
| >2.5 mm           | 250 °C                      | 245 °C                            | 245 °C                       |

| Profile feature   | Standard SnPb solder | Lead (Pb) free solder |
|---|----------------------|-----------------------|
| Preheat and soak  |                      |                       |
| • Temperature min. ( $T_{smin}$ )   | 100 °C               | 150 °C                |
| • Temperature max. ( $T_{smax}$ )   | 150 °C               | 200 °C                |
| • Time ( $T_{smin}$ to $T_{smax}$ ) ( $t_s$ )                                     | 60-120 seconds       | 60-120 seconds        |
| Ramp up rate $T_L$ to $T_P$   | 3 °C/ second max.    | 3 °C/ second max.     |
| Liquidous temperature ( $T_L$ )   | 183 °C               | 217 °C                |
| Time ( $t_L$ ) maintained above $T_L$   | 60-150 seconds       | 60-150 seconds        |
| Peak package body temperature ( $T_P$ )*  | Table 1              | Table 2               |
| Time ( $t_p$ )* within 5 °C of the specified classification temperature ( $T_C$ ) | 10 seconds*          | 10 seconds*           |
| Ramp-down rate ( $T_P$ to $T_L$ )   | 6 °C/ second max.    | 6 °C/ second max.     |
| Time 25 °C to peak temperature  | 6 minutes max.       | 8 minutes max.        |

\* Tolerance for peak profile temperature ( $T_P$ ) is defined as a supplier minimum and a user maximum.

Life Support Policy: Eaton does not authorize the use of any of its products for use in life support devices or systems without the express written approval of an officer of the Company. Life support systems are devices which support or sustain life, and whose failure to perform, when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.

Eaton reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Eaton also reserves the right to change or update, without notice, any technical information contained in this bulletin.

**Eaton**  
Electronics Division  
1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
Eaton.com/electronics

© 2023 Eaton  
All Rights Reserved  
Printed in USA  
Publication No. ELX1271 BU-ELX22134  
January 2023

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Follow us on social media to get the latest product and support information.

