


SPECIFICATION CONTROL DRAWING



MATERIALS

1. **INSULATION SLEEVE:** Heat-shrinkable, transparent blue, radiation cross-linked modified polyvinylidene fluoride.
2. **SOLDER PREFORM WITH FLUX:**
SOLDER: TYPE Sn63 per ANSI J-STD-006.
FLUX: TYPE ROL1 per ANSI-J-STD-004.

APPLICATION

1. This part is designed to be used in conjunction with a Raychem AS-4000 Wire Organization System to attach tin or silver plated wires to connector terminals on 2.54 (0.100) or greater centers.
Wire Accommodation:
 Jacket O.D.: 1.73 (0.068) max.
 Gauge: 30 - 24 gauge
Connector Terminal:
 Max. Width: 1.73 (0.068)
 Min. Height: 3.81 (0.150)
2. Sleeve will recover to 0.64 (0.025) max. I.D.

| | | | | | | | |
|---|---|---|-----------------|--|------------|------------------|--|
| Raychem Interconnect <small>a division of tyco ELECTRONICS</small> 300 Constitution Drive Menlo Park, CA 94025, USA | | THERMOFIT DEVICES | | TITLE: SOLDERSLEEVE WIRE TERMINATOR TAB TERMINAL (AS-4000) | | | |
| UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS. INCHES DIMENSIONS ARE BETWEEN BRACKETS. | | | | DOCUMENT NO.: D-128-0028 | | | |
| TOLERANCES: 0.00 N/A 0.0 N/A 0 N/A | ANGLES: N/A ROUGHNESS IN MICRON | Raychem reserves the right to amend this drawing at any time. Users should evaluate the suitability of the product for their application. | | DCR NUMBER: D990752 | | REPLACES: N/A | |
| DRAWN BY: M. FORONDA | DATE: 06-July-00 | PROD. REV. B | DOC ISSUE: 1 | SCALE: None | SIZE: A | SHEET: 1 of 1 | |

If this document is printed it becomes uncontrolled. Check for the latest revision.