

## Printed-circuit board connector - DFK-PC 5/ 9-G-7,62 - 1727650

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)

Header, Nominal current: 41 A, Rated voltage (III/2): 630 V, Number of positions: 9, Pitch: 7.62 mm, Color: green, Contact surface: Tin, Assembly: Soldering



### Product Features

- Panel thickness of 1 mm to 3 mm
- Mounted on the housing panel by means of tool-free snap-lock mechanism or conventional screw connection
- For soldering onto the PCB
- Feed-through headers for use in combination with all PC 5 plugs



### Key commercial data

|                                      |           |
|--------------------------------------|-----------|
| Packing unit                         | 1 pc      |
| Minimum order quantity               | 10 pc     |
| Weight per Piece (excluding packing) | 22.22 GRM |
| Custom tariff number                 | 85366990  |
| Country of origin                    | Poland    |

### Technical data

#### Dimensions

|                |           |
|----------------|-----------|
| Length         | 29.25 mm  |
| Pitch          | 7.62 mm   |
| Dimension a    | 60.96 mm  |
| Pin dimensions | 0,8 x 1,0 |
| Pin spacing    | 7.62 mm   |
| Hole diameter  | 1.3 mm    |

#### General

|                           |                |
|---------------------------|----------------|
| Range of articles         | DFK-PC 5/...-G |
| Insulating material group | I              |

# Printed-circuit board connector - DFK-PC 5/ 9-G-7,62 - 1727650

## Technical data

### General

|   |        |
|---|--------|
| Rated surge voltage (III/3)             | 6 kV   |
| Rated surge voltage (III/2)             | 6 kV   |
| Rated surge voltage (II/2)              | 6 kV   |
| Rated voltage (III/3)                   | 500 V  |
| Rated voltage (III/2)                   | 630 V  |
| Rated voltage (II/2)                    | 800 V  |
| Connection in acc. with standard        | EN-VDE |
| Nominal current I <sub>N</sub>          | 41 A   |
| Maximum load current                    | 41 A   |
| Insulating material                     | PA     |
| Inflammability class according to UL 94 | V0     |
| Color                                   | green  |
| Number of positions                     | 9      |

## Classifications

### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 272607xx |
| eCl@ss 4.1 | 27260701 |
| eCl@ss 5.0 | 27260701 |
| eCl@ss 5.1 | 27141190 |
| eCl@ss 6.0 | 27260704 |
| eCl@ss 7.0 | 27440402 |
| eCl@ss 8.0 | 27440402 |

### ETIM

|          |          |
|----------|----------|
| ETIM 3.0 | EC001121 |
| ETIM 4.0 | EC002637 |
| ETIM 5.0 | EC002637 |


### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211810 |
| UNSPSC 7.0901 | 39121409 |
| UNSPSC 11     | 39121409 |
| UNSPSC 12.01  | 39121409 |
| UNSPSC 13.2   | 39121409 |


## Drawings

# Printed-circuit board connector - DFK-PC 5/ 9-G-7,62 - 1727650

Drilling diagram




Dimensioned drawing



Sheet metal cutout for snap-on.

Dimensioned drawing



Sheet metal cutout for screw connection.

Dimensioned drawing

