



Model: USB-32COM-RM

32 Port RS-232 USB-to-Serial Adapter

A rack mountable industrial USB to 32 Port RS-232 serial adapter that allows you to add thirty two RS-232 serial ports by connecting to a single USB host port.

C€ F©

Specifications		
Serial Interface	32 x RS232	
Ports	32	
Speed	Up to 921.6kbps	
Available Modes	RS232 full duplex, RS422 full duplex, RS485 4 wire, full duplex, RS485 2 wire, half duplex, with echo, RS485 2 wire, half duplex, without echo	
Signals	TxD, RxD, RTS, CTS, DTR, DSR, DCD, GND	
USB Interface	USB 2.0	
Power	Self powered, Built-in power supply 110-240V AC 47-63 Hz, 25VA	
Driver	Windows 2000 to Windows 8 (x86 and x64), Windows Server 2000 to 2008 R2 (x86 and x64) Linux (Kernel 2.6 built-in, 2.4 available)	
Connectors	32 RJ45 ports	
Dimensions	429 x 147 x 44 mm (W×L×H), 451 x 147 x 44 mm (with DIN-Rail ears)	
Approvals	EMC: FCC Class A, CE Class A	
Environmental	Operating Temperature 0 to 55 °C (32 to 131 °F) Operating Humidity 5 to 95% RH Storage Temperature -20 to 75 °C (-4 to 167 °F)	

Features	Product Information	
 Metal case Rack and DIN-Rail mountable RS232 RJ45 ports Speed up to 921.6kbps Built-in power supply 	Product Name: Packing List: Optional Accessories:	USB-32COM-RM USB-32COM-RM Adapter, USB cable 0,9m, Serial Adapter cables, Power cord N/A