# BGA Heat Sink - High Performance maxiFLOW w/Thermal Tape



ATS Part#:

Description:

#### ATS-52150P-C1-R0

15.00 x 15.00 x 17.50 mm BGA Heat Sink - High Performance maxiFLOW w/Thermal Tape

Heat Sink Type:maxiFLOWHeat Sink Attachment:Thermal TapeEquivalent Part Number:ATS-52150P-C2-R0

\*Image above is for illustration purpose only.

### **Features & Benefits**

- maxiFLOW<sup>™</sup> design features a low profile, spread fin array that maximizes surface area for more effective convection (air) cooling
- Fabricated from extruded aluminum, which minimizes thermal resistance from the base to the fins, reduces weight and keeps costs low
- Higher performance helps ensure reliable product life at a lower cost than other extruded heat sinks

## **Thermal Performance**

		@200 LFM 1.0 M/S	@300 LFM 1.5 M/S	@400 LFM 2.0 M/S	@500 LFM 2.5 M/S	@600 LFM 3.0 M/S	@700 LFM 3.5 M/S	@800 LFM 4.0 M/S
THERMAL RESISTANCE	Unducted Flow	8.7 °C/W	7.2 °C/W	6.3 °C/W	5.7 °C/W	5.2 °C/W	4.9 °C/W	4.6 °C/W
	Ducted Flow	7.1	N/A	N/A	N/A	N/A	N/A	N/A

## **Product Detail**

Schematic Image	Dimension A	Dimension B	Dimension C	Dimension D	ТІМ	Finish
	15.00 mm	15.00 mm	17.50 mm	30.56 mm	T412	BLUE-ANODIZED
	<ul> <li>Dimension</li> <li>ATS-5215 (Saint-Gol</li> <li>Thermal p application</li> <li>ATS resen performant</li> <li>ATS certifi</li> </ul>	i0P-C2-R0 is the exa bain C675). performance data are n. rves the right to upda nce. ies that this heat sin	imponent size. leight from the bottor act heat sink assemb e provided for referer ate or change its prod k assembly is RoHS istom options availab	ly with an equivalent nce only. Actual perfo ducts without notice -6 and REACH comp	t thermal	interface material may vary by
*Image above is for illustration purpose only.						

For more information, to find a distributor or to place an order, please contact us at 781-769-2800 (North America), **sales@qats.com** or **www.qats.com**.

