# NSYTBS19128T

ABS box IP66 IK07 RAL7035 Int.H175W105D80 Ext.H191W121D87 Transp.cover H20





#### Main

Range	Thalassa
Product name	Thalassa TBS
Device Application	Multi-purpose
Category	Industrial box
Height	7.56 in (192 mm)
Width	4.76 in (121 mm)
Depth	3.43 in (87 mm)
Internal height	6.89 in (175 mm)
Internal width	4.13 in (105 mm)
Internal depth	3.15 in (80 mm)
Enclosure mounting	Wall mounted
Device composition	1 body
	1 cover 4 cover screw
	4 Cover screw
Quantity per Set	Set of 2
Body type	One piece moulded
Type of front cover	Low transparent cover
Cover fixing	Plastic screws
Lock type	Captive screw flat outside sealed area
Removable parts	Cover by captive screws

#### Complementary

Complementary		
Material	ABS (acrylonitrile butadiene-styrene)	
Color	Gray RAL 7035)	
	Transparent	
Standards	IEC 62208	
Product Certifications	TÜV	
Electrical Insulation Class	Class II	
IP degree of protection	IP66 conforming to NEMA 4.4X	
IK degree of protection	IK07 IEC 62262	
Glow wire resistance	1202 °F (650 °C) IEC 60695-2-11	
Ambient Air Temperature for Storage	5104 °F (-1540 °C)	
Operating temperature	-13140 °F (-2560 °C)	
Net Weight	0.84 lb(US) (0.38 kg)	

#### Ordering and shipping details

80033-ENCLOSURE SYSTEMS POLYESTER
ES1
3606480165443
1
13.40 oz (380.0 g)
No
HU

# Packing Units

•	
Unit Type of Package 1	PCE
Package 1 Height	3.94 in (10.0 cm)
Package 1 width	7.87 in (20.0 cm)
Package 1 Length	10.24 in (26.0 cm)
Unit Type of Package 2	CAR
Number of Units in Package 2	28
Package 2 Weight	25.04 lb(US) (11.36 kg)
Package 2 Height	15.75 in (40.0 cm)
Package 2 width	23.62 in (60.0 cm)
Package 2 Length	11.02 in (28.0 cm)

## Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	<sup>₽</sup> REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS  Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₽¥Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

### Contractual warranty

Warranty	18 months
----------	-----------