



SS Stainless Steel

Metric table

Dimensions in: millimeters - inches

1 d ₁	2 d ₂ Thread	3 l ₁					l ₂		d ₃		d ₄	h ₁	h ₂
		10	15	20	25	-	MS tip	KU tip	MS tip	KU tip			
25 0.98	M 5	0.39	0.59	0.79	0.98	-	0.5 0.02	1 0.04	3 0.12	3 0.12	12 0.47	16 0.63	8 0.31
32 1.26	M 6	0.39	0.63	0.79	0.98	1.18	1 0.04	1.3 0.05	4 0.16	3.5 0.14	14 0.55	20 0.79	10 0.39
40 1.57	M 8	0.79	0.98	1.18	1.57	1.97	1.5 0.06	1.6 0.06	6 0.24	5 0.20	18 0.71	25 0.98	13 0.51
50 1.97	M 10	0.79	0.98	1.18	1.77	2.17	2 0.08	1.9 0.07	8 0.31	6.5 0.26	22 0.87	32 1.26	17 0.67

Specification

- Star knob DIN 6336
Plastic
Technopolymer (Polyamide PA)
Black, matte finish
- Threaded stud
Stainless steel AISI 304 Cu
- Tip
 - Brass **MS**
 - Plastic (Polyacetal POM) **KU**
- Plastic Characteristics → page 2135
- Stainless Steel Characteristics → page 2143
- RoHS compliant

Information

GN 6336.10 star knobs with stainless steel threaded stud are an excellent choice for corrosion-free applications.

The brass or plastic tip on the stud prevents indentations or other damage from occurring.

see also...

- Hollow Knurled Knobs GN 421.10 (with Brass / Plastic Tip) → www.jwwinco.com
- Wing Screws EN 633.10 (with Plastic Tip) → www.jwwinco.com
- Hollow Knurled Knobs GN 7336.5 (with Brass / Plastic Tip) → www.jwwinco.com
- Star Knobs GN 6336.10 with Loss Protection GN 111.7 → page 2046

<p>How to order</p> <p>1 2 3 4</p> <p>GN 6336.10-32-M6-20-KU</p>	1	Handle diameter d ₁
	2	Thread d ₂
	3	Length l ₁
	4	Tip material