

# 4300V Series

# Tubeaxial

## 119x119x32mm VARIOFAN



- DC fans with electronically commutated external rotor motor. Fully integrated commutation electronics.
- With electronic protection against reverse polarity, blocking and overloading by PTC-resistor partially impedance protected.
- Temperature sensor (LZ370) must be ordered separately.
- Mounting from either face using four 4.3 mm holes.

- Fan of fiberglass reinforced plastic. PBTP housing, PA impeller.
- Air exhaust over struts. Rotational direction CW looking at rotor.
- Electrical connection via 3 leads AWG 22, TR 64. Stripped and tinned ends.
- UL, CSA, VDE approvals on some models, please contact application engineering.

Part Number	CFM @ 0	VDC	Volt. Range	Power (W)	dBA	Max Amb. Temp C	Bearing Type	Features	Wgt. (lbs)
4312MV	40-82	12	8 to 13	1.5-3.0	22-39	65	Ball	Leads	0.5
4312V	50-100	12	8 to 13	2.4-5.5	29-45	65	Ball	Leads	0.5
4314V	50-100	24	21 to 27	3.0-5.4	29-45	65	Ball	Leads	0.5
4318V	40-100	48	40 to 53	2.6-5.4	21-45	65	Ball	Leads	0.5

