

NOTES, UNLESS OTHERWISE SPECIFIED:

PANDUIT CT-1701 TOOL:

TOOL WEIGHT: 20 oz. [0,56] kg

Crimps Panduit #10 - #2 AWG non-insulated P series terminals and #14 - 10 AWG copper code conductor lugs. Includes 5-position, rotating die.

Provides UL Listed and CSA Certified terminations with applicable Panduit terminals.

DIMENSIONS SHOWN IN BRACKETS [] ARE METRIC, AND ARE FOR REFERENCE ONLY.

	ENG	GLISH	METRIC			
DIE	GO / NO GO GAGE		GO / NO GO GAGE MEMBERS			
INDEX	MEN	/ BERS				
NUMBER	"G" Dia.	"NG" Dia.	"G" Dia.	"NG" Dia.		
	(GO)	(NO GO)	(GO)	(NO GO)		
P10	0.099"	0.109"	2,51 mm	2,76 mm		
P8	0.179"	0.201"	4,54 mm	5,10 mm		
P6	0.217"	0.238"	5,51 mm	6,04 mm		
P4	0.273″	0.295"	6,93 mm	7,49 mm		
P2	0.351"	0.374"	8,91 mm	9,49 mm		

		CT-1701 Contour Crimp™ Crimping Tool						
		ITEM REVISION NAME:						
		TP2	3827C	01_0	2	PAND	UIT	
GO CHART.		UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE:				MATERIAL:		
AL LOGO FROM GRIP, GERMANY TO FRAME.	4857/02	(.x) ± (.xx) ±	(.xxx) ANGL					
BRANDING	4857		THIRD ANGLE PROJECTION			DRAWING NUMBER: TP23827C01		
SCRIPTION	ECN	drawn by: BLR	DATE: 5-08-15	CHK BJPU	SCALE NONE	SHT 1 OF 1	SIZE C	