

Aug. 1.2023 Copyright 2023 HIROSE ELECTRIC CO., LTD. All Rights Reserved.  
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

APPLICABLE STANDARD					
RATING	OPERATING TEMPERATURE RANGE	-25 °C TO +85 °C	STORAGE TEMPERATURE RANGE	-10 °C TO +60 °C	
	VOLTAGE	_____	_____	_____	
	CURRENT	_____	APPLICABLE CABLE	φ 10±0.5mm	
SPECIFICATIONS					
ITEM	TEST METHOD		REQUIREMENTS	QT	AT
CONSTRUCTION					
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.		ACCORDING TO DRAWING.	X	X
MARKING	CONFIRMED VISUALLY.			-	-
ENVIRONMENTAL CHARACTERISTICS					
CORROSION SALT MIST	EXPOSED IN 5 % SALT WATER SPRAY FOR 500 h.		NO HEAVY CORROSION RUIN THE FUNCTION.	X	-
SEALING <sup>(1)</sup>	EXPOSED AT A DEPTH OF 1.8 m FOR 48 h.		NO WATER PENETRATION INSIDE CONNECTOR.	X	-
AIRTIGHTNESS <sup>(1)</sup>	APPLY AIR PRESSURE 18 kPa FOR 0.5min TO INSIDE CONNECTOR.		NO AIR BUBBLES INSIDE CONNECTOR.	X	-
	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
REMARK			APPROVED	HY. KOBAYASHI	18.02.26
NOTES(1) SEALING AND AIRTIGHTNESS SHALL BE TESTED BY APPLICABLE CONNECTOR			CHECKED	HY. KOBAYASHI	18.02.26
			DESIGNED	TH. KAMEYA	18.02.23
Unless otherwise specified, refer to JIS C 5402.(IEC 60512)			DRAWN	MK. INOUE	18.02.23
Note QT:Qualification Test AT:Assurance Test X:Applicable Test			DRAWING NO.		ELC-110458-31-00
	SPECIFICATION SHEET		PART NO.	JR13WCC-10 (31)	
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL114-2051-3-31	1/1