

1	2	3	4	5	6	7																																																								
A	B	C	D	E	F	G																																																								
<p>1</p>																																																														
<p>RoHS compliant Unit: mm</p> <p>File No.: E349947</p>																																																														
<table border="1"> <thead> <tr> <th>Scale</th> <th>Free</th> <th colspan="2"></th> <th colspan="2"></th> <th></th> </tr> </thead> <tbody> <tr> <td colspan="2">TOLERANCE</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>X.</td> <td>±0.50</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>X.X</td> <td>±0.30</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>X.XX</td> <td>±0.10</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td colspan="2">DIM</td> <td>TOL</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>X.°</td> <td>±1°</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Angle</td> <td>TOL</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>							Scale	Free						TOLERANCE							X.	±0.50						X.X	±0.30						X.XX	±0.10						DIM		TOL					X.°	±1°						Angle	TOL					
Scale	Free																																																													
TOLERANCE																																																														
X.	±0.50																																																													
X.X	±0.30																																																													
X.XX	±0.10																																																													
DIM		TOL																																																												
X.°	±1°																																																													
Angle	TOL																																																													
<table border="1"> <thead> <tr> <th>Id.</th> <th>Modification</th> <th>Date</th> <th>Name</th> <th colspan="3"></th> </tr> </thead> <tbody> <tr> <td>①</td> <td>Update to new drawing and add UL</td> <td>15.03.2016</td> <td>Amy</td> <td></td> <td></td> <td></td> </tr> <tr> <td>②</td> <td>Updating</td> <td>19.04.2010</td> <td>Alex</td> <td></td> <td></td> <td></td> </tr> </tbody> </table>							Id.	Modification	Date	Name				①	Update to new drawing and add UL	15.03.2016	Amy				②	Updating	19.04.2010	Alex																																						
Id.	Modification	Date	Name																																																											
①	Update to new drawing and add UL	15.03.2016	Amy																																																											
②	Updating	19.04.2010	Alex																																																											
<table border="1"> <thead> <tr> <th>Date</th> <th>Name</th> <th>Customer-No.</th> <th colspan="4"></th> </tr> </thead> <tbody> <tr> <td>Drawn</td> <td>19.04.2010</td> <td>Alex</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Approved</td> <td>15.03.2016</td> <td>Amy</td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>							Date	Name	Customer-No.					Drawn	19.04.2010	Alex					Approved	15.03.2016	Amy																																							
Date	Name	Customer-No.																																																												
Drawn	19.04.2010	Alex																																																												
Approved	15.03.2016	Amy																																																												
<p>ASSMANN WSW-Components</p> <p>ASSMANN WSW-No. A-TB100-TM04</p> <p>Drawing-No. ASS 2011A CO rev01</p> <p>Replace Sheet</p>																																																														
<p>Electrical</p> <p>cULus VDE</p> <p>Voltage rating: 400VAC / 450VAC</p> <p>Current rating: 10A / 24A</p> <p>Wire range: 0.34-2.5mm²</p> <p>Solid wire(AWG): 14-22</p> <p>Stranded wire(AWG):14-22</p> <p>Torque(Lb-In): 3.5 / 0.5</p> <p>Screw: M3</p> <p>Wire strip length: 7-8mm</p> <p>Withstanding Voltage: 1.8KV/2.5KV</p> <p>Operating temperature: -40°C to +115°C</p> <p>Safety Approval: </p>																																																														
<p>Material</p> <p>① Terminal body(metal housing of double): Brass(CuZn),Ni plated</p> <p>② Terminal body(metal housing of single): Brass(CuZn),Ni plated</p> <p>③ Terminal screw: Steel Zinc plating "-" slot type</p> <p>④ Wire guard(short): Stainless steel</p> <p>⑤ Insulator(lever): Thermoplastic (UL94V-0)</p> <p>⑥ Insulator(housing): Thermoplastic (UL94V-0)</p> <p>⑦ Wire guard(long): Stainless steel</p>																																																														