

ODU MINI-SNAP□ Series L Plug acc. IEC 60601-1

General information

| | |
|------------------------|---|
| Part number | SB2LAC-P12PFG2-720S |
| Termination | Crimp |
| Size | 2 |
| Locking principle | push ✖ |
| Coding | a_key |
| Cable Diameter | cable_mini_72 |
| Cable outlet | bend_relief |
| customs tariff numbers | 85366990 |

| | | |
|-------------------------------|-------------------------------|-------------------------------|
| <input type="text" value=""/> | <input type="text" value=""/> | <input type="text" value=""/> |
|-------------------------------|-------------------------------|-------------------------------|

Contact insert description

| | |
|--------------------|-----------|
| Number of contacts | 12 |
| Contact type | pins |
| Contact diameter | 07mm |
| Insulator material | peek |
| Wire cross section | 22-26 AWG |
| Termination | Crimp |

Technical information

| | | |
|--|----------|---------------|
| Max. creepage and air clearance distance | 12_mm | 2_moop |
| Nominal current single contact | 075_a | iec_60512_5_2 |
| Nominal current insert | 4,1 A | vde_0298_14 |
| Test voltage | 12_kv_ac | sae_13441 |

safety_text

Mechanical and environmental data

| | |
|-----------------------|----------|
| Degree of protection* | ip50 |
| Operating temperature | 40_120_c |
| Mating cycles | 5000 |

mated_unmated

Material and surface treatments

| | |
|---------|---------------|
| Housing | chrome_finish |
| Contact | cu_alloy_gold |

safety_text_2
ul_text
illustrative_text