

FCI P/N	C P/N	L/mm
10121797-P0025YYLF	A5E31328448	250±2
10121797-P0035YYLF	A5E31434525	345±2

A

B

C

D

A



B

C

D

P1

P2



②

①

②	IDC CONN.	Minitek 2x15 position IDC receptacle, 0.76um gold, with central key and friction latch bump	2	PC
①	RIBBON CABLE	UL2651, 28AWGx30C, Pitch1.0, Grey PVC,	A/R	M
No.	NAME	DESCRIPTION	QTY	UNIT
www.fciconnect.com		surface - ✓ tolerance std - - projection	mm	
		TOLERANCES UNLESS OTHERWISE SPECIFIED		
Dr	Tom Feng	2012-11-16	ANGULAR	LINEAR
Eng	Tom Feng	2012-11-16	0.X	±-
Chr	Roger Cheng	2012-11-16	0.XX	±-
Appr	Jackson Wang	2012-11-16	0.XXX	±-
Product family		size A3		Scale 2:3
Spec ref		ECN		-
		title Minitek IDC Cable Ass'y	dwg no 10121797	Rev. A
catalog no -		CUSTOMER		sheet 1 of 1

NOTES:

1. TEST:

□/S:100% TEST.
 CONNECTION RESISTANCE: 3.0 OHM MAX.
 HI-POT:300V/10mS.
 INSULATION RESISTANCE: 10 MOHM MIN.

2. ROHS COMPLIANCE

rev	ecn no	dr	date
A	-	TF	2012-11-16

REV F - 2006-04-17

1

2

3

PDS: Rev :A

STATUS:Released

4

Printed: Nov 19, 2012



Copyright FCI.