



2370-2380 MHz Cavity Bandpass Filter

Part Number: AB2375B999



ANATECH ELECTRONICS INC
RF & Microwave Filters & Products

Electrical specifications

- Center Frequency:** 2375 MHz
- Bandwidth:** 10 MHz
- Input / Output Impedance:** 50 Ohms
- Passband:** 2370 – 2380 MHz
- Passband over bandwidth:** <0.5 dB
- Passband Insertion Loss:** <1.0 dB
- Passband Ripple:** <0.2 dB
- Passband Return Loss:** >20dB
- Rejection:** 13 MHz offset from Center Frequency > 20dBc
- Rejection 2:** 20 MHz offset from Center Frequency > 30dBc
- Power Handling:** 20 W (avg)
- Peak Power Handling:** 150 W
- Group Delay variation over bandwidth:** <5 ns


Mechanical

- Mounting Method:** Threaded Mounting Holes
- Connector Type:** SMA (F)
- Dimensions:** 6.19 x 5.52 x 1.58 Inches

Environmental

- Operating Temperature:** 0 to +55 deg.C
- Storage Temperature:** -45 to +85 deg.C
- Shock:** 20 G. 11ms
- Vibration:** 20 G. 5 to 200 Hz

Outline Drawing:



DS-B999-03152018-Rev0