

In case of consideration for using Autom otive equipm ent/device which dem and high reliability, kindly contactour sales w indow correspondents.

APPLICABLE STANDARD		STORAGE TEMPERATURE RANGE	
OPERATING TEMPERATURE RANGE	-35 °C TO +85°C (NOTE1)	STORAGE TEMPERATURE RANGE	-10 °C TO +60°C (NOTE3)
OPERATING HUMIDITY RANGE	20% TO 80% (NOTE2)	STORAGE HUMIDITY RANGE	40% TO 70% (NOTE3)
VOLTAGE	50 V AC/DC	VOLTAGE	50 V AC/DC
CURRENT		CURRENT	
NUMBER OF CONTACTS	AWG28 AWG30 AWG32 AWG34	NUMBER OF CONTACTS	AWG28 AWG30 AWG32 AWG34
2	2.5A 1.5A 1.0A 0.8A	2	2.5A 1.5A 1.2A 1.0A
3	2.0A 1.5A 1.0A 0.8A	3	2.0A 1.5A 1.2A 1.0A
4,5,6	1.5A 1.0A 0.8A 0.5A	4,5,6	1.5A 1.0A 1.0A 1.0A
APPLICABLE CONNECTOR CONTACT	DF57H-*P-1.2V(##) DF57-2830SCF DF57-3234SCF	OPERATING TEMPERATURE RANGE	-35 °C TO +75°C (NOTE1)

SPECIFICATIONS

ITEM

TEST METHOD

REQUIREMENTS

QT AT

CONSTRUCTION	TEST METHOD	REQUIREMENTS	QT	AT
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X
MARKING	CONFIRMED VISUALLY.		X	X

ELECTRIC CHARACTERISTICS

INSULATION RESISTANCE	100 V DC.	100 MΩ MIN.	X	—
VOLTAGE PROOF	500 V AC FOR 1 min.	NO FLASHOVER OR BREAKDOWN.	X	—

MECHANICAL CHARACTERISTICS

MECHANICAL OPERATION	30 TIMES INSERTION AND EXTRACTION.	NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	—
VIBRATION	FREQUENCY 10 TO 55 Hz, SINGLE AMPLITUDE 0.75 mm, AT 10 CYCLES FOR 3 DIRECTION.	NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	—
SHOCK	490 m/s ² DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.		X	—

ENVIRONMENTAL CHARACTERISTICS

DAMP HEAT(STEADY STATE)	EXPOSED AT 40 ± 2°C , 90 TO 95 % , 96 h. (AFTER LEAVING THE ROOM TEMPERATURE FOR 1-2h.)	① INSULATION RESISTANCE: 100 MΩ MIN. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	—
RAPID CHANGE OF TEMPERATURE	TEMPERATURE -55°C→ +85°C TIME 30min→ 30min UNDER 5 CYCLES. (THE TRANSFERRING TIME OF THE TANK IS 2-3 min) (AFTER LEAVING THE ROOM TEMPERATURE FOR 1-2h.)	① INSULATION RESISTANCE: 100 MΩ MIN. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	—

REMARKS

NOTE 1: INCLUDE THE TEMPERATURE RISING BY CURRENT.
NOTE2:NO CONDENSING
NOTE3:APPLY TO THE CONDITION OF LONG TERM STORAGE FOR UNUSED PRODUCTS BEFORE PCB ON BOARD, AFTER PCB BOARD, OPERATING TEMPERATURE AND HUMIDITY RANGE IS APPLIED FOR INTERIM STORAGE DURING TRANSPORTATION.

COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
1	DIS-H-008817	TS. KUMAZAWA	TS. FUKUSHIMA	14.06.13
		APPROVED	KI. AKIYAMA	12.11.21
		CHECKED	HK. UMEHARA	12.11.21
		DESIGNED	TS. KUMAZAWA	12.11.21
		DRAWN	TS. KUMAZAWA	12.11.21

Unless otherwise specified, refer to IEC 60512.

Note QT:Qualification Test AT:Assurance Test X:Applicable Test

DRAWING NO.

ELC4-349275-01

HRS SPECIFICATION SHEET		PART NO.	DF57H-*S-1.2C(08)
HIROSE ELECTRIC CO., LTD.		CODE NO.	CL666-
			△
			1/1