



SITOP PSU8600/1AC/24VDC/20A/4X5A PN

SITOP PSU8600 1AC 20 A/4x5 A PN stabilized power supply input: 100-240 V AC output: 24 V DC/20 A/4x 5 A with PN/IE connection web server integrated OPC UA server integrated *Ex approval no longer available*

Input	
type of the power supply network	1-phase and 2-phase AC or DC
supply voltage at AC	
<ul style="list-style-type: none"> • minimum rated value • maximum rated value • initial value • full-scale value 	100 V 240 V 85 V 275 V
supply voltage	
<ul style="list-style-type: none"> • at DC 	110 ... 220 V
input voltage	
<ul style="list-style-type: none"> • at DC 	93 ... 275 V
design of input wide range input	Yes
operating condition of the mains buffering	at $V_{in} = 100\text{ V}$; Prioritized supply Output 1 at power failure can be selected via DIP switch
buffering time for rated value of the output current in the event of power failure minimum	20 ms
operating condition of the mains buffering	at $V_{in} = 100\text{ V}$; Prioritized supply Output 1 at power failure can be selected via DIP switch
line frequency	
<ul style="list-style-type: none"> • 1 rated value • 2 rated value 	50 Hz 60 Hz
line frequency	47 ... 63 Hz
input current	
<ul style="list-style-type: none"> • at rated input voltage 100 V • at rated input voltage 120 V • at rated input voltage 230 V • at rated input voltage 240 V • at rated input voltage 110 V • at rated input voltage 220 V 	5.4 A 4.5 A 2.5 A 2.4 A 4.8 A 2.4 A
current limitation of inrush current at 25 °C maximum	15 A
I ² t value maximum	4.33 A ² ·s
fuse protection type	internal
<ul style="list-style-type: none"> • in the feeder 	required: circuit breaker (for UL: UL489-listed/DIVQ) characteristic C, 10-32 A, alternatively slow-response fuses (for UL: UL248-listed)
Output	
voltage curve at output	Controlled, isolated DC voltage
number of outputs	4
output voltage at DC rated value	24 V
output voltage	
<ul style="list-style-type: none"> • at output 1 at DC rated value 	24 V

<ul style="list-style-type: none"> • at output 2 at DC rated value • at output 3 at DC rated value • at output 4 at DC rated value 	24 V 24 V 24 V
relative overall tolerance of the voltage	3 %
relative control precision of the output voltage <ul style="list-style-type: none"> • on slow fluctuation of input voltage • on slow fluctuation of ohm loading 	0.2 % 0.1 %
residual ripple <ul style="list-style-type: none"> • maximum 	100 mV
voltage peak <ul style="list-style-type: none"> • maximum 	200 mV
adjustable output voltage	4 ... 28 V
product function output voltage adjustable	Yes
type of output voltage setting	via potentiometer or IE/PN interface; Derating > 24 V: 4%/V; max. 120 W per output, max. 480 W overall system
display version for normal operation	3-color LED for operating state device; LED for operating mode manual/remote; 4 LEDs for communication PROFINET; 3-color LED per output for operating state output; LED green for parallel operation Output 1 and 2 / 3 and 4
type of signal at output	Relay contact (changeover contact, contact current capacity DC 60 V/0.3 A) for "Operating state OK"
behavior of the output voltage when switching on	No overshoot of Vout (soft start)
response delay maximum	1 s; Without on-delay of the outputs
type of outputs connection	Simultaneous connecting-in of all outputs after device booting or delay time of 25 ms, 100 ms or "load-optimized" for sequential cutting-in of the outputs via DIP switches can be set
voltage increase time of the output voltage <ul style="list-style-type: none"> • maximum 	500 ms
output current <ul style="list-style-type: none"> • rated value • per output • at output 1 rated value • at output 2 rated value • at output 3 rated value • at output 4 rated value • rated range 	20 A 5 A 5 A 5 A 5 A 5 A 0 ... 20 A
supplied active power typical	480 W
product feature <ul style="list-style-type: none"> • parallel switching of outputs • bridging of equipment 	Yes; Parallel circuit Output 1 with 2 or Output 3 with 4 can be selected via DIP switch No
Efficiency	
efficiency in percent	92 %
power loss [W] <ul style="list-style-type: none"> • at rated output voltage for rated value of the output current typical • during no-load operation maximum 	39 W 14 W
Closed-loop control	
relative control precision of the output voltage with rapid fluctuation of the input voltage by +/- 15% typical	0.1 %
relative control precision of the output voltage load step of resistive load 50/100/50 % typical	0.4 %
setting time <ul style="list-style-type: none"> • maximum 	10 ms
Protection and monitoring	
design of the overvoltage protection	max. 35 V (max. 500 ms)
property of the output short-circuit proof	Yes
design of short-circuit protection	electronic overload cut-off; optionally constant current operation can be selected for Output 4 via DIP switches
adjustable current response value current of the current-dependent overload release	0.5 ... 5 A
type of response value setting	via potentiometer or IE/PN interface
switching characteristic	

<ul style="list-style-type: none"> of the excess current 	$I_a > 1.0 \dots < 1.5 \times I_a$ threshold permissible for 5 s; I_a limit (= $1.5 \times I_a$ threshold) permissible for 200 ms
<ul style="list-style-type: none"> of the current limitation 	I_a limit (= $1.5 \times I_a$ threshold) permissible for 5 s, afterwards I_a threshold continuous
design of the reset device/resetting mechanism	via sensor per output or IE/PN interface
remote reset function	Non-electrically isolated 24 V input (signal level "high" at > 15 V)
overcurrent overload capability in normal operation	Total system overloadable 150% I_a rated to 5 s/min
display version for overload and short circuit	3-color LED for operating state device; 3-color LED per output for operating state output

Interface

design of the interface	Ethernet/PROFINET
<ul style="list-style-type: none"> PROFINET protocol 	Yes
protocol is supported OPC UA	Yes

Safety

galvanic isolation between input and output	Yes
galvanic isolation	Safety extra-low output voltage U_{out} acc. to EN 60950-1 and EN 50178
operating resource protection class	Class I
leakage current	
<ul style="list-style-type: none"> maximum 	3.5 mA
protection class IP	IP20

Approvals

certificate of suitability	
<ul style="list-style-type: none"> CE marking UL approval 	Yes
<ul style="list-style-type: none"> CSA approval 	Yes; cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259; cCSAus (CSA C22.2 No. 60950-1, UL 60950-1)
<ul style="list-style-type: none"> cCSAus, Class 1, Division 2 ATEX 	No; cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259; cCSAus (CSA C22.2 No. 60950-1, UL 60950-1)
certificate of suitability	
<ul style="list-style-type: none"> IECEX NEC Class 2 ULhazloc approval FM registration 	No
type of certification CB-certificate	Yes
certificate of suitability	
<ul style="list-style-type: none"> EAC approval C-Tick 	Yes
certificate of suitability shipbuilding approval	No
Marine classification association	
<ul style="list-style-type: none"> American Bureau of Shipping Europe Ltd. (ABS) French marine classification society (BV) DNV GL Lloyds Register of Shipping (LRS) Nippon Kaiji Kyokai (NK) 	No

EMC

standard	
<ul style="list-style-type: none"> for emitted interference for mains harmonics limitation for interference immunity 	EN 55022 Class B EN 61000-3-2 EN 61000-6-2

environmental conditions

ambient temperature	
<ul style="list-style-type: none"> during operation during transport during storage 	-25 ... +60 °C; with natural convection -40 ... +85 °C -40 ... +85 °C
environmental category according to IEC 60721	Climate class 3K3, 5 ... 95% no condensation

Mechanics

type of electrical connection	Plug-in terminals with screwed connection
<ul style="list-style-type: none"> at input 	L1/+, N/L2/-, PE: Plug-in terminal with 1 screwed connection each for 0.2 ... 4 mm ² single-wire / fine stranded
<ul style="list-style-type: none"> at output 	1, 2, 3, 4: Two plug-in terminals (1, 2 and 3, 4) with 2 screwed

<ul style="list-style-type: none"> • for auxiliary contacts • for signaling contact 	<p>connections each for 0.2 ... 2.5 mm²; 0 V: Plug-in terminal with 3 screwed connections for 0.2 ... 4 mm²</p> <p>RST (Reset): Plug-in terminal (together with alarm signal) with 1 screwed connection for 0.2 ... 1.5 mm²</p> <p>11, 12, 14 (alarm signal): Plug-in terminal (together with Reset) with 1 screwed connection each for 0.2 ... 1.5 mm²</p>
product function	Yes
<ul style="list-style-type: none"> • removable terminal at input • removable terminal at output 	Yes
design of the interface for communication	PROFINET/Ethernet: two RJ45 sockets (2-port switch)
suitability for interaction modular system	Yes
width of the enclosure	125 mm
height of the enclosure	125 mm
depth of the enclosure	150 mm
required spacing	
<ul style="list-style-type: none"> • top • bottom • left • right 	<p>50 mm</p> <p>50 mm</p> <p>0 mm</p> <p>0 mm</p>
net weight	2.6 kg
product feature of the enclosure housing can be lined up	Yes
fastening method	Snaps onto DIN rail EN 60715 35x15
electrical accessories	Expansion modules CNX8600, buffer modules BUF8600, module UPS8600
mechanical accessories	Device identification label 20 mm × 7 mm, TI-grey 3RT2900-1SB20
MTBF at 40 °C	186 700 h
other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)

