

**Data sheet | Item number: 770-131**

Locking lever; for flying leads; for tool operation; white

[www.wago.com/770-131](http://www.wago.com/770-131)



**Color:**

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG  
Hansastr. 27  
32423 Minden  
Phone: +49571 887-0 | Fax: +49571 887-169  
Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
We are always happy to take your call at +49 (571) 887-44222.



## Item description

### Locking system *WINSTA*® MIDI

When using the locking system from the *WINSTA*® MIDI product line, zero-defect installation is ensured. You can rely on the level of quality of *WINSTA*® components from WAGO for your electrical installation accessories too. *WINSTA*® MIDI with Push-in CAGE CLAMP® spring pressure connection technology is used in can be found in a variety of projects you can use for quick, easy, secure, tailored electrical installation.

### *WINSTA*® MIDI solutions for your electrical installation – maintenance-free

*WINSTA*® is the pluggable connection system that is ideally tailored to the strict requirements of electrical installation. It offers error-free installation of cables and components, quickly and reliably. Choose durability and quality – the *WINSTA*® MIDI accessory from WAGO makes the electrical installation of electrical components significantly easier.

- 
- for automation controllers
- quick replacement of defective units during ongoing operation

## Data

### Connection data

#### Connection 1

Actuation type

Operating tool

### Mechanical Data

Suitable

for flying leads; tool operated

### Material Data

Note (material data)

Information on material specifications can be found here

Color

white

Insulation material

Polyamide (PA66)

Flammability class per UL94

V0

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG

Hansastr. 27

32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169

Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.



Fire load	0.013 MJ
Weight	0.4 g

### Environmental requirements

Processing temperature	-5 ... +40 °C
Continuous operating temperature	-35 ... +85 °C
Note on continuous operating temperature	Insulating parts for temperatures ≤ 105 °C

### Commercial data

Product Group	20 (Winsta)
eCl@ss 10.0	27-44-06-92
eCl@ss 9.0	27-44-06-92
ETIM 8.0	EC002863
ETIM 7.0	EC002863
PU (SPU)	100 (25) pcs
Packaging type	box
Country of origin	DE
GTIN	4017332755245
Customs tariff number	85389099990

### Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

### Approvals / Certificates

#### General approvals

Logo	Approval	Additional Approval Text	Certificate name
	VDE VDE Prüf- und Zertifizierungsinstitut	EN 61535	40029808

### Downloads

#### Documentation

##### Bid Text

770-131	2019 年2月19 日	xml	Download
X81 - Datei		2.7 kB	

Subject to changes. Please also observe the further product documentation!



770-131  
doc - Datei

2015 年3月11 日

doc  
22.0 kB

Download

## CAD/CAE-Data

### CAD data

2D/3D Models 770-131

URL

Download

### CAE data

WSCAD Universe 770-131

URL

Download

ZUKEN Portal 770-131

URL

Download

## Environmental Product Compliance

### Compliance Search

Environmental Product Compliance 770-131

URL

Download

Locking lever; for flying leads; for tool operation; white

## Installation Notes

### Product family

WINSTA® MIDI

[Show all products from the family](#)

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG

Hansastr. 27

32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169

Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.