

ELECTRO ACOUSTIC TRANSDUCER

BRT1615P-C SERIES

ROHS COMPLIANT

SPECIFICATIONS





Model No.	BRT1615P-01-C	BRT1615P-06-C	BRT1615P-12-C
Rated Voltage (VDC)	1.5	6	12
Operating Voltage (VDC)	1.2 ~ 2	4 ~ 7	8 ~ 16
Rated Current (mA)	MAX.20	MAX. 30	
Sound Output @10 cm(dB)	MIN. 75	MIN. 85	
Resonant Frequency (Hz)	2,300	2,200	
Operating Temperature (°C)	-20 to +70		
Storage Temperature (°C)	-30 to +80		
Housing Material	Noryl SE1-GFN2J		
Weight (g)	7.0		

FEATURES (With Circuit)


- Sealed design for soldering and flux washing
- Low current consumption



CHARACTERISTICS



DIMENSIONS



Wave Solder And Wash Allowed

Tolerance: ± 0.5 mm

APPLICATIONS

Microwave oven, electronic cash register, printers, telephone, timer, pocket pager, POS systems, computer peripherals, keyboard, copy machine, automobile electronics, portable battery operated equipment.

INTERVOX
International ©

INTERNATIONAL COMPONENTS CORPORATION
215 MCCORMICK DRIVE, BOHEMIA, NY 11716
FAX: 631-952-9595 FAX: 631-952-9597

Title:

Electro Acoustic Transducer

Code:
G82

Intervox Model #
BRT1615P-C SERIES

Rev
A

Scale:
mm

Date:
2/15/2006

Sheet 1 of 1