

## **Technical Data Sheet**

## 4-Port RS-232 USB to Serial Adapter Data Control Box

**Model Number: USB-4COM** 







The USB-4COM adds 4 RS-232 serial ports via an available USB port, the serial adapter control box uses FTDI and is automatically detected. The 4-Port RS-232 USB to Serial Adapter provides instant connectivity with modems, ISDN TAs, PDAs, handheld & pocket PC's, digital cameras, POS, serial printers. It is suitable for remote access, retail and industrial applications, data collection and other applications requiring high speed RS-232 serial communication ports.

## **Features**

- TAA Compliant.
- Adds four high speed RS-232 serial ports.
- Rugged plastic housing with built-in LED status indicators for TxD and RxD.
- Installed as standard Windows COM port.
- Full RS-232 modem control signals and hardware/software flow control.
- Non-standard baud rates supported.
- Serial port protected with surge protection of 10KV.
- Powered by USB port.
- Easy plug-and-play installation.
- COM port number assigned can be changed.

## **Product Information**

- Model Number: USB-4COM
- Packing List:
  - o USB to Serial RS-232 Adapter
  - o 3ft. USB-A male to USB-B male cable
  - o Driver Disk
- Optional Accessories: N/A



- Works with USB 1.1 & 2.0 host port
- Supports Windows 8, Windows 7, Vista, 2003, XP, 2000 and Linux.

ne	CIT	ıcatı	ions
 ~~	CIII	Cut	I O I I S

Specifications						
Overview						
Interface	USB to Serial					
Port Connections	4x DB-9 Male / 1USB Type-B Female					
Protections	10KV surge protection					
USB Speed	JSB 1.0 / 1.1 compliant, USB 2.0 compatible up to 480Mbps					
Protocol	RS-232					
Baud Rate	up to 921.6K bps					
Available Power Modes	usb Bus Powered, no external power adapter required					
Color	Silver					
Compliance	TAA					
Physical Features						
Construction	Plastic					
Cable Length	3ft.					
Dimensions	5.43(L) x 5.12(W) x 1.56in(H)					
Weight	.468 lbs					
OS Support	Windows 8, Windows 7, Vista, 2003, XP, Linux.					
Signals						
RS-232 Data Signals	TxD, RxD, RTS, CTS, DSR, DTR, DCD, RI, GND					
Indicators						
LED	built-in LED status indicators for TxD and RxD					
<b>General Applications</b>						
Applications	Modem use, ISDN TAs, PDAs, handheld & pocket PC's, digital cameras, POS, serial printers, suitable for remote access and others.					
Product URL						
USB-4COM product page	https://www.coolgear.com/product/4-port-rs-232-usb-serial-adapter-data-control-box					