

BT series
TIMER BTDS-S
Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com



BTDS installation timing relays for star/delta switchover in machine applications.

The timing relay is built into an Insta enclosure just 17.5 mm wide.

The relay contact is designed as a changeover contact with 250 V/5 A switching capacity.

General ordering data

Order No.	8647660000
Type	TIMER BTDS-S
Version	BT series, Timing relay, No. of contacts: 2, NO contact, AgNi 90/10, Rated control voltage: 24...230 V AC, 24...48 V DC, Continuous current: 5 A, Screw connection
GTIN (EAN)	4032248308866
Qty.	1 pc(s).

BT series
TIMER BTDS-S

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data**Ratings**

Conductor connection system	Screw connection	Humidity	35...85 % rel. humidity, no condensation
UL 94 flammability rating	V-2		

Dimensions and weights

Width	17.5 mm	Height	80 mm
Depth	73 mm	Net weight	80 g

Temperatures

Operating temperature	-10 °C...+55 °C	Storage temperature	-25 °C...+65 °C
-----------------------	-----------------	---------------------	-----------------

Input

Rated control voltage	24...230 V AC, 24...48 V DC	Power rating	≤ 0.4 VA, 1.6 W
Time ranges	0.10 s - 120 h	Repeat accuracy	± 1 %

Output

Max. switching voltage, AC	250 V	Continuous current	5 A
----------------------------	-------	--------------------	-----

Contact specifications

No. of contacts	2	Contact design	NO contact
Contact material	AgNi 90/10	Mechanical service life	10 ⁷ switching cycles (no load, 1800/h)
Electrical service life, DC coil	10 ⁵ switching cycles (5A at 250 Vac, ohm load at 1800/h)	Contact resistance	100 MΩ min., at 500 V DC

Insulation coordination

Protection degree	IP 30 // terminals IP 20
-------------------	--------------------------

Other technical data

Version	Timing relay
---------	--------------

Further details of approvals / standards

Certificate No. (UR)	E223474OMR	Standards	UL508
----------------------	------------	-----------	-------

Rated data UL

Certificate No. (UR)	E223474OMR
----------------------	------------

Classifications

ETIM 2.0	EC001439	ETIM 3.0	EC001439
UNSPSC	30-21-19-17	eClass 4.1	27-14-23-10
eClass 5.1	27-14-23-10	eClass 6.0	27-14-23-10
eClass 7.0	27-14-23-10		

Data sheet...

**BT series
TIMER BTDS-S**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Technical data

Approvals

Approvals



Downloads

Declaration of Conformity [K258_08_03.pdf](#)