## **Bolt End Cutting Nippers**

high lever transmission DIN ISO 5743

61

## Powerful, compact, comfortable

- > features a greater cutting capacity and requires less effort than conventional end cutting nippers
- > cuts nails, small bolts and all wires including piano wire
- > exceptional cutting capacity due to high leverage joint
- > cutting edge hardness (approx. 64 HRC)
- > vanadium steel; forged, multi stage oil-hardened

## 61 02 200

Slim two-color multi-component sleeves for better handling and easier transport; large contact surface on the handles for better allotment of pressure and more comfort at work



High cutting performance: also for piano wire



61 01 200 \$\langle 5^c \rightarrow\$





Perfect for working with fencing



Almost flush cutting of bolts, nails, etc.

							Cutting capacities				
		<b>←→</b>									
		Inch					Ø Inch	Ø Inch	Ø Inch	Ø Inch	
Product Number	Packaging	mm		Pliers	Head	Handles	Ø mm	Ømm	Ømm	Ømm	lbs
61 01 200	X 8 200	8	/F0 <b>A</b>	black atramentized	polished	plastic coated	3/64 - 15/64	5/32	9/64	1/8	0.96
		<u>∡</u> 5° ► black	black attamentized polisned	polistieu	plastic coated	1.0 - 6.0	4.0	3.5	3.0	0.96	
61 02 200		8 200 ∡5° ▶ ■ black atramentize	black atromontized	polished	slim multi-component grips	3/64 - 15/64	5/32	9/64	1/8	1.03	
			DIACK attamentized	polistied		1.0 - 6.0	4.0	3.5	3.0		

## High Leverage End Cutting Nippers DIN ISO 5748



- > cutting edges for soft, hard and piano wire
- > high cutting capacity with minimal effort due to optimum coordination of cutting edge angle and transmission ratio
- > cutting edge hardness (approx. 64 HRC)
- > chrome vanadium heavy-duty steel; forged, multi stage oil-hardened





							Cutting capacities				
Product Number	Packaging	<b>d→</b> Inch mm		Pliers	Head	Handles	Ø Inch Ø mm	Ø Inch Ø mm	Ø Inch Ø mm	Ø Inch Ø mm	∆'∆ Ibs
67 01 140		5 1/2 140	•			plastic coated	5/32 4.0	1/8 3.1	5/64 2.0	1/16 1.5	0.34
67 01 160		6 1/4 160		black atramentized	polished		11/64 4.5	9/16 3.4	3/32 2.5	5/64 2.0	0.52
67 01 200	Х	<mark>8</mark> 200						13/64 5.0	5/32 3.8	1/8 3.0	3/32 2.5