



Hologen Free

L301314A Series



1. Features of L301314A Series :

- Alloy powder core is used to realize lower core loss.
- No thermal aging concerns.
- Low leakage magnetic flux.
- Elimination for impulse (EMI) noise.
- Ideally used as Power Factor Correction choke.
- Also can be used as boost inductor in power supplies.
- Inductance Range: 69.63uH to 300 uH , custom values are welcomed.
- Foot Print 29.0×26.0mm max. , 16.5mm max. Height.
- Operating Temperature Range: -55°C to + 130°C; RoHs & HF compliance.




2. Electrical Characteristics of L301314A Series:


ITG Part Number	OCL (PIN1-2) ¹	DCR	Isat ²	L@Isat	Irms ³	L@Irms	Dim. A	Dim. D
	(uH) ± 15%	(mΩ) Max. @25°C	(A) @25°C	(uH) @25°C	(A) @25°C	(uH) @25°C	(mm) Max.	(mm) Max.
L301314A-690LHF	69.63	18.50	3.80	47.29	9.50	19.40	29.00	16.50
L301314A-101LHF	100.00	26.00	3.20	68.54	8.00	28.33	29.00	16.50
L301314A-151LHF	150.00	43.00	2.60	102.26	6.00	47.29	28.00	16.00
L301314A-201LHF	200.00	75.00	2.20	137.68	4.50	74.73	28.00	15.50
L301314A-251LHF	250.00	112.00	2.00	169.05	3.60	104.82	27.00	14.50
L301314A-301LHF	300.00	170.00	1.80	205.34	2.90	143.64	27.00	14.50

3. Mechanical Dimension of L301314A Series (Unit:mm):




A	B	C	D	E1	E2	F
Max.	± 0.30	± 0.50	Max.	± 0.50	± 0.50	± 0.10
See table above	25.70	3.20	See table above	20.32	20.32	Φ1.00



Top View



Front View



Bottom View

The diameter of hole of Base:14.0; ±0.5mm



Notes:

1. Open Circuit Inductance (OCL) and L@Irms and L@Isat are measured at 100KHz,0.25V@ 25°C.
2. Isat: DC current that causes inductance to drop by approximately 35% from OCL (Ta=25°C).
3. Irms: DC current that causes an approximate temperature rise (ΔT) of 40°C (Ta=25°C).

● New York 1 914 347 2474 ● Taipei 886 2 2698 8669 ● Kaohsiung 886 7 350 2275
 ● Japan 81 568 85 2830 ● Shenzhen 86 755 8418 6263 ● Shanghai 86 21 5424 5141 ● Hong Kong 852 9688 9767
 ● sales@ITG-Electronics.com ● www.ITG-Electronics.com Revision A.0: August 1, 2019

*Due to continuous product improvement, all specifications are subject to change without prior notice. Kindly contact an ITG field application engineer or a sales representative prior to purchase.



4. Inductance vs. Current vs. Temperature Rise Characteristics of L301314A Series :

