

- NOTES:
1. MATERIALS: HOUSING - LIQUID CRYSTAL POLYMER (LCP), GLASS-FILLED, UL94V-0
TERMINALS - HIGH PERFORMANCE COPPER ALLOY
 2. FINISH: 30µIN MIN GOLD IN CONTACT AREA, SELECTIVE TIN ON PCB TAILS, NICKEL OVERALL.
 3. REFER TO MOLEX PRODUCT SPEC PS-76060-999 FOR PERFORMANCE SPECIFICATIONS AND ADDITIONAL PCB INFORMATION.
 4. EACH SIGNAL WAFER CONTAINS 2 COLUMNS OF TERMINALS.
 5. PRODUCT IS PACKAGED PER PK-70873-589.
 6. THIS PART CONFORMS TO CLASS B REQUIREMENTS OF COSMETIC SPEC PS-45499-002.
 7. REFER TO MOLEX SALES DRAWING SD-76145-001 FOR THE MATING HEADERS AND SD-76460-001 FOR MATING RAM.
 8. REFER TO MOLEX PCB ROUTING GUIDE AS-76060-990 FOR ANTIPAD AND ROUTING RECOMMENDATIONS.
 9. PART NUMBER 76150-1020 SHOWN ON DRAWING. KEYING FEATURES WILL CHANGE WITH COLUMN SIZE.
 10. MINIMUM BOARD THICKNESS IS 1.00 mm FOR COMPLIANT PIN FUNCTIONALITY.
 11. MARKING: LOCATED APPROXIMATELY AS SHOWN. PART NUMBER AND DATE CODE.

DAUGHTERCARD HOLE PATTERN (CONNECTOR SIDE)

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION									
DIMENSION UNITS		SCALE		CURRENT REV DESC: MIGRATED TO NX					
mm		NTS		<p>IMPACT 100 OHM DC 6 PAIR SIGNAL MODULE UNGUIDED SALES DRAWING</p> <p>PRODUCT CUSTOMER DRAWING</p>					
GENERAL TOLERANCES (UNLESS SPECIFIED)									
ANGULAR TOL ± 0.5°									
4 PLACES ±									
3 PLACES ±									
2 PLACES ± 0.13				EC NO: 622829		2019/08/22		<p>DOCUMENT NUMBER</p> <p>SD-76150-001</p> <p>DOC TYPE DOC PART REVISION</p> <p>PSD 001 G3</p>	
1 PLACE ± 0.25				DRWN: PKH		2019/08/29			
0 PLACES ±				CHK'D: BOKOK		2019/08/30			
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS				APPR: SHONG		2019/08/30			
THIRD ANGLE PROJECTION				INITIAL REVISION:		2006/12/11			
DRAWING				DRWN: JLAURX		2008/04/24		MATERIAL NUMBER	
C-SIZE				APPR: JLAURX		76150		CUSTOMER	
SERIES				DRAWING		GENERAL MARKET		SHEET NUMBER	
76150				C-SIZE		76150		1 OF 2	



MATERIAL NUMBER	# OF COLUMNS	# OF DIFF PAIR	DIM "A" MAX	DIM "B"	PTH ϕ
76150-*010	10	60	19.00	17.10	0.46 ± 0.05
76150-*014	14	84	26.60	24.70	
76150-*016	16	96	30.40	28.50	
76150-*020	10	60	19.00	17.10	0.39 ± 0.05
76150-*024	14	84	26.60	24.70	
76150-*026	16	96	30.40	28.50	

76150- * 0 **

1 = OPEN LEAD-FREE

OF COLUMNS
 10 = 10 COL 0.46 PTH
 14 = 14 COL 0.46 PTH
 16 = 16 COL 0.46 PTH
 20 = 10 COL 0.39 PTH
 24 = 14 COL 0.39 PTH
 26 = 16 COL 0.39 PTH

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

DIMENSION UNITS		SCALE		CURRENT REV DESC: MIGRATED TO NX					
mm		NTS							
GENERAL TOLERANCES (UNLESS SPECIFIED)				EC NO: 622829		IMPACT 100 OHM DC 6 PAIR SIGNAL MODULE UNGUIDED SALES DRAWING			
ANGULAR TOL $\pm 0.5^\circ$				DRWN: PKH 2019/08/22					
4 PLACES \pm				CHK'D: BOKOK 2019/08/29					
3 PLACES \pm				APPR: SHONG 2019/08/30		PRODUCT CUSTOMER DRAWING			
2 PLACES ± 0.13				INITIAL REVISION:		DOCUMENT NUMBER			
1 PLACE ± 0.25				DRWN: JLAURX 2006/12/11		SD-76150-001		DOC TYPE	
0 PLACES \pm				APPR: JLAURX 2008/04/24		PSD		DOC PART	
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS				THIRD ANGLE PROJECTION		C-SIZE		SERIES	
						76150		REVISION	
DOCUMENT STATUS				P1		RELEASE DATE		2019/08/30 15:04:20	
12				11		10		9	
8				7		6		5	
4				3		2		1	