



Non-Invasive

Accurately reads elevated moisture content using cutting edge electromagnetic wave technology that penetrates 1½” through most materials. Non-destructive leaving no marks and automatically calibrates to dry air. The probe can be held at any angle and reads 0 to 100% moisture in wood and drywall for building inspection, lumber, water damage repair, and other industries. The large LCD simultaneously displays current, maximum and minimum moisture content, has a bright backlight and a low battery indicator. Features adjustable audible and visible, Hi/Lo wetness risk alarm, auto-power-off and a hold function. Comes ready to use with clear instructions and 3 AAA batteries.

DIM: 9½" × 2½" × 1" (242 × 63 × 30 mm). WEIGHT: 8 oz (226 g).

No.	Description
850002	Scanning Moisture Meter



	Materials	Resolution	Accuracy
Moisture Content	All soft and hard woods including but not limited to Pine, Poplar, Oak, Maple, and Teak.	0.1%	±2%
	All forms of drywall and sheetrock including cementboard, ¼" and ½" gypsum drywall, soundboard, and greenboard.		
NOTE: This meter is not appropriate for testing concrete, brick, mortar, or screed			
Operating Temperature and Humidity	0 to 40°C And less than 85% Relative Humidity		
Reading Depth Range	40 mm		
Power Supply	AAA, 1.5V battery x 3		
Battery Life	200 hours without backlight 50 hours with backlight constantly on.		