



- NOTES:**
- 1- JACK FOR MATING WITH SHIELDED PLUG (MOLEX 95043 AND 85568 SERIES)
  - 2- PRODUCT SPECIFICATION: PS-95122
  - 3- APPLICATION SPECIFICATION: AS-95001
  - 4- PACKAGING SPECIFICATION: PK-95122 SHEET 2 (BLISTER ON REEL)
  - 5- P.C.B THICKNESS: 1.57/0.62
  - 6- COPLANARITY OF SIGNAL LEADS: 0.10 MAX
- TECHNICAL SPECIFICATIONS:**
- MATERIAL:**
- HOUSING: POLYAMIDE GLASS FILLED UL 94V-0  
COLOUR BLACK
- TERMINAL: PHOSPHOR BRONZE PLATED WITH:  
0.00127/.000050 MIN GOLD IN CONTACT AREA,  
0.00190/.000075 MIN PURE TIN IN TAIL  
AREA, BOTH OVER 0.00127/.000050 MIN NICKEL  
OVERALL.
- SHIELD: BRASS PLATED WITH 0.0020/.000078 MIN TIN.

MODIFIED VIEWS EC NO: E2006-0826 2006/04/06 DRWN:DBYRNES 2006/04/06 CHKD: APPR:EOMAHONY 2006/04/11	QUALITY SYMBOLS ▽=0 ▽=0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE	SCALE	DESIGN UNITS	THIRD ANGLE PROJECTION		
				MM/IN	4:1	METRIC			
				mm	INCH	TITLE			
				ANGULAR ± 2 °		FULLY SHIELDED SMT R/A MODULAR JACKS 8 CKT			
L REV	DESCRIPTION	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		DRAWN BY	DATE	MATERIAL NO.			
				KUBATIN	2003/07/28	95122-6882			
				CHECKED BY	DATE	DOCUMENT NO.			
				ECHTENA	2003/07/28	SD-95122-005			
				APPROVED BY	DATE	SHEET NO.			
				HEIM	2003/07/28	1 OF 1			
				MOLEX INCORPORATED THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION					