

Aug. 1.2023 Copyright 2023 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

| APPLICABLE STANDARD | | | | | | |
|--|---------------------------------------|--------------------------|---------------------------|-------------------|------------------|-----|
| Rating | Operating Temperature Range | -25°C to +60°C | Storage Temperature Range | -25°C to +60°C | | |
| | Voltage | — | Operating Humidity Range | — | | |
| | Curent | — | Applicable Cable | — | | |
| SPECIFICATIONS | | | | | | |
| ITEM | TEST METHOD | REQUIREMENTS | QT | AT | | |
| CONSTRUCTION | | | | | | |
| General Examination | Visually and by measuring instrument. | According to drawing. | X | X | | |
| Marking | Confirmed visually. | | X | X | | |
| | | | | | | |
| | COUNT | DESCRIPTION OF REVISIONS | DESIGNED | CHECKED | DATE | |
| | 0 | | | | | |
| REMARK | | | APPROVED | NM. NISHIMATSU | 17. 02. 07 | |
| | | | CHECKED | NM. NISHIMATSU | 17. 02. 07 | |
| | | | DESIGNED | MO. SHIMOYAMA | 17. 02. 07 | |
| Unless otherwise specified, refer to IEC 60512. | | | DRAWN | JY. IGA | 17. 02. 07 | |
| Note QT:Qualification Test AT:Assurance Test X:Applicable Test | | | DRAWING NO. | | ELC-120682-06-00 | |
| HRS | SPECIFICATION SHEET | | PART NO. | TM11APA1-88P (06) | | |
| | HIROSE ELECTRIC CO., LTD. | | CODE NO. | CL222-2783-4-06 | | 1/1 |