



SS Stainless Steel

Metric table

Dimensions in: millimeters - inches

| 1 d ₁ | 2 d ₂ Thread | 3 Length l | | | | | b | h |
|---------------------|-------------------------------|---------------|------------|------------|------------|------------|--------------|------------|
| | | 6 | 10 | 16 | 25 | 30 | | |
| 20 0.79 | M 4 | 6 0.24 | 10 0.39 | - | - | - | 9.5 0.37 | 11 0.43 |
| 25 0.98 | M 5 | 10 0.39 | 16 0.63 | 25 0.98 | - | - | 11 0.43 | 13 0.51 |
| 32 1.26 | M 6 | 10 0.39 | 16 0.63 | 20 0.79 | 25 0.98 | 30 1.18 | 13 0.51 | 15 0.59 |
| 32 1.26 | M 8 | 16 0.63 | 20 0.79 | 25 0.98 | 30 1.18 | 40 1.57 | 13 0.51 | 15 0.59 |
| 40 1.57 | M 8 | 16 0.63 | 25 0.98 | 40 1.57 | - | - | 15.5 0.61 | 17 0.67 |
| 48 1.89 | M 8 | 16 0.63 | 25 0.98 | - | - | - | 19 0.75 | 19 0.75 |
| 56 2.20 | M 10 | 20 0.79 | 30 1.18 | - | - | - | 21 0.83 | 23 0.91 |

Specification

- Wing body
Plastic
Technopolymer (Polyamide PA)
- Glass fiber reinforced
- Temperature resistant up to 266 °F (130 °C)
- Black, matte finish
- Threaded stud
Stainless steel AISI 303 **NI**
- Plastic Characteristics → page 2135
- Stainless Steel Characteristics → page 2143
- RoHS compliant

Information

Due to their low height EN 531 wing screws offer a comfortable grip for quick two finger clamping applications.

Resistant to solvents, oils, grease and other chemical agents.

see also...

- Wing Screws GN 433 (Stainless Steel) → page 678
- Wing Screws GN 431 (Stainless Steel) → page 679

| How to order | 1 |
|---------------------------|--------------------------------|
| EN 531-32-M6-30-NI | Handle diameter d ₁ |
| | Thread d ₂ |
| | Length l |
| | Material |