


SPECIFICATION CONTROL DRAWING



Product Revision		Product Dimensions			Usable Wire Gauge	
Product Name		L max	ØA min	ØB min	Straight Splice	End Splice
C-110-0058	B	27.6 (1.090)	2.7 (0.105)	3.2 (0.125)	20 - 22	N/A

MATERIALS

1. INSULATION SLEEVE: Heat-shrinkable, transparent blue, radiation cross-linked modified polyvinylidene fluoride.
2. SOLDER PREFORM WITH FLUX:
 SOLDER: TYPE Sn63 per ANSI J-STD-006.
 FLUX: TYPE ROM1 per ANSI J-STD-004.

APPLICATION

1. The parts covered by this SCD are for use in splicing tin or silverplated solid conductors of the sizes listed.
2. Parts will meet the requirements of AT&T Specification KS-21256L2 and Raychem Specification RT-1404 when installed per Raychem Installation Procedure RPIP-823-00.
3. Temperature rating: -55°C to +125°C.

tyco Electronics 307 Constitution Drive Menlo Park, CA 94025		Raychem		TITLE : KS21256-L2 Soldersleeve Device			
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS. INCHES DIMENSIONS ARE BETWEEN BRACKETS.				DOCUMENT NO.: C-110-0058			
TOLERANCES: 0.00 N/A 0.0 N/A 0 N/A	ANGLES: N/A ROUGHNESS IN MICRON	Raychem reserves the right to amend this drawing at any time. Users should evaluate the suitability of the product for their application.		DCR NUMBER: D010004		REPLACES: D980611	
DRAWN BY: M. FORONDA	DATE: 18-Jan.-01	PROD. REV. See table	DOC ISSUE: 2	SCALE: None	SIZE: A	SHEET: 1 of 1	

If this document is printed it becomes uncontrolled. Check for the latest revision.