PART NUMBER	SSF-LXH409SYSUGW	REV.	Α
DATE	E.C.N. NUMBER AND REVISION COMMENTS		REV.
12.28.12	E.C.N. #10BRDR. & REDRAWN.		Α

TYP

590 (YELLOW)

574 (GREEN)

 $I_f = 20 \text{mA}$

UNITS

nm

nm

MAX

Α

TEST COND

	4.0 [0.157] -	7.77 [0.306]
- 7.00 [0.276]	-	
ø4.00 [ø0.157] —	─ ø3.00 [ø0.118]	
5.08 [0.200] # LUMEX	7.62 [0.300]	(E)
0.50 [0.020]	3.18 [0.125]	1)—
0.50 [0.020] SQR. (3 PLS.)	2.54 [0.100] (2 PLS.)	1.27 [0.050]

	FORWARD VOLTAGE (V/O)	00/00 05/00	14.
	FORWARD VOLTAGE (Y/G)	2.0/2.2 2.5/2.6	Vf
	REVERSE VOLTAGE 5.0		V _r I _r =100µA
′	AXIAL INTENSITY (Y/G)	250/80	mcd If=20mA
	VIEWING ANGLE	60	2x theta
	EMITTED COLOR: YELLOW/GR	EEN	
/ <u> </u>	EPOXY LENS FINISH: MILKY WHIT	E	
6.0 [0.234]			
3.0 20.23 13	LIMITS OF SAFE OPERATION AT 25	· C	
4 07 50 0503			


ELECTRO-OPTICAL CHARACTERISTICS TA=25°C

MIN

YELLOW ③ OFEEN

2

COMMON
CATHODE



EIMITS OF SALE OF EIVATION AT 200					
Х					
4					

* t<10µS

PARAMETER

PEAK WAVELENGTH

NOTES:

- 1. SSH-LXH409, BLACK HOLDER.
- 2. SSL-LX3059SYSUGW, BICOLOR LED.

*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN= $^{+0.00}_{-0.00}$



25 N. CARY AVE.
CAROL STREAM, II. 60188-4900
PHONE: 1-1800.278.5666
FAX: +1.630.315.2152
WEB: WWW.LUMEX.COM
MEMBER OF *TWV* PHOTONICS GROUP

T-4mm RIGHT ANGLE INDICATOR, 3 LEADS, COMMON CATHODE, AlinGaP YELLOW/GREEN BICOLOR, WHITE DIFFUSED L

THE SPECIFICATIONS MAY CHANGE AT ANY TIME WITHOUT NOTICE DUE TO NEW MATERIALS OR PRODUCT IMPROVEMENT.

CONFIDENTIAL INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. SEPECHFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DESEMBATION TO ALL THIRD PARTIES.

E	ν₿ΆΤΕ:	12.28.12	DRAWN BY:	MA
	PAGE:	1 OF 1	CHKD BY:	DT
	SCALE:	NTS	APRVD BY:	DT
	UNIT:	mm [INCH]	P	