



Product: <u>5302F1</u> ☑

Security & Sound, #18-4c, TC, Shielded, CMG-FPL-PLTC, Water-Blocked

Product Description

Security & Sound Cable, Rated-CMG-FPL-PLTC, 4-18 AWG stranded tinned copper conductors with PVC insulation, waterblocking tape, Beldfoil® shield and PVC jacket

Technical Specifications

Product Overview

Suitable Applications:	Security System, Intercom/PA, Audio/Speaker, Pov	wer-Limited Controls, Noisy & Wet Location, Below-Grade Duct
Construction Details		
Conductor		
Element No. of Elements	Size Stranding Material	
Conductor(s) 4	18 AWG 7x26 TC - Tinned Copper	
	II	
Insulation Element Material	Nom. Thickness Nom. Insulation Diame	ter Color Code
	Chloride 0.010 in (0.25 mm) 0.066 in (1.7 mm)	Black, White, Red, Green
Outer Shield	Destantia Tara	
Shield TypeMaterialTapeBi-Laminate (Alui	Coverage Drainwire Type n+Poly) 100% 20 AWG (7x28) TC	
Waterblocking:	Waterblock Tape	
Waterblocking.	Waterblock Tape	
Outer Jacket		
	. Thickness Nom. Diameter	
	in (0.94 mm) 0.259 in (6.58 mm)	
Overall Cable Diameter (Nomina	il): 0.259 in (6.58 mm)	
Electrical Characteristi	cs	
Electricals		
Element Nom. Conducto	r DCR Nom. Capacitance Cond-to-Cond	
Conductor(s) 6.6 Ohm/1000ft	40 pF/ft (130 pF/m)	
/altana		
Voltage UL Voltage Rating		
300 V (CMG, FPL, PLTC-ER)		
Mechanical Characteris		

UL Temperature	Operating	
105°C	-30°C to +105°C	

Bend Radius

Stationary Min. Installation Min.

2.6 in (66 mm) 2.6 in (66 mm)	
Max. Pull Tension:	102 lbs (46.3 kg)
Bulk Cable Weight:	45 lbs/1000ft

Standards and Compliance

Environmental Suitability:	Water Exposure/Below-Grade Conduit, Indoor, Outdoor, Sunlight Resistance, Burial
Flammability / Reaction to Fire:	UL 1685 FT4 Loading, FT4, IEEE 1202
CPR Compliance:	CPR Euroclass: Eca
NEC / UL Compliance:	Article 725, Article 760, Article 800, CMG, FPL, PLTC
CEC / C(UL) Compliance:	CMG
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
UK Regulation Compliance:	UKCA Mark
APAC Compliance:	China RoHS II (GB/T 26572-2011)

History

Update and Revision: Revision Number: 0.458 Revision Date: 04-14-2023

Part Numbers

Variants

ltem #	Color	Putup Type	Length	UPC	Footnote
5302F1 0101000	Black	Reel	1,000 ft	612825159599	С
5302F1 0021000	Red	Reel	1,000 ft	612825159582	С

© 2023 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.