

## USB 3.0 SuperSpeed to SATA III Adapter for 2.5 in. to 3.5 in. SATA Hard Drives

MODEL NUMBER: **U338-000-SATA**



Format new hard drives, or salvage data off old drives

### Description

Tripp Lite's U338-000-SATA USB 3.0 SuperSpeed to SATA III Adapter allows connection to a Serial ATA Hard drive (2.5" / 3.5" ). Configure hard drives without having to install them first, or, pull data from a crashed computer hard drive to a new computer. The unit features a 22-Pin SATA Data + Power connector, and USB 3.0 Micro-B connector . Works with any 2.5 in. to 3.5 in. SATA Hard Drive. The U338-000-SATA is compatible with Windows (up to 10) and Mac, and can be connected to older USB generation computers ( 2.0 and 1.1, at slower speeds )

### Features

- USB 3.0 and below compliant
- SATA III ( 6Gbps ) and below compliant
- Supports Plug-and-Play...No Drivers or Software needed
- Supports LBA-48 bit ( Logical Block Addressing )
- Supports USB Mass Storage Class Bulk-Only Transport
- 22-Pin SATA Data + Power connector
- Compatible with 2.5" / 3.5" SATA Hard drives
- Supports drives up to 4TB
- Compatible with Windows (up to 10), Mac, Linux

## Specifications

OVERVIEW	
UPC Code	037332182135
Technology	SATA/eSATA

### Highlights

- SuperSpeed (5Gbps) / Hi-Speed (480 Mbps) / Full-Speed (12 Mbps) Compliant
- SATA III (6Gbps) / SATA Gen2i (3Gbps) / Gen1i (1.5Gbps) Compliant
- For 2.5 in. to 3.5 in. SATA Hard Drives
- Supports drives up to 4TB
- Compatible with Windows (up to 10), MAC, LINUX

### System Requirements

- Computer with USB 3.0 port ( 2.0 and 1.1 compatible, but at slower transfer speeds )
- SATA 2.5" or 3.5" Hard Drive

### Package Includes

- U338-000-SATA USB 3.0 SuperSpeed to SATA III Adapter
- USB 3.0 Micro-B Cable, 2.5 ft.
- External Power Supply with NEMA 1-15P Plug ( Input: 100-240V, 50/60Hz, 0.8A; Output: 12V, 2A )

<b>POWER</b>	
AC Adapter	Input: 100-240V, 50/60Hz, 0.8A; Output: 12V, 2A
<b>PHYSICAL</b>	
Color	Black
Shipping Dimensions (hwd / in.)	3.00 x 3.20 x 5.00
Shipping Dimensions (hwd / cm)	7.62 x 8.13 x 12.70
Shipping Weight (lbs.)	0.56
Shipping Weight (kg)	0.25
<b>ENVIRONMENTAL</b>	
Operating Temperature Range	-4 to 140 F (-20 to 60 C)
Storage Temperature Range	-4 to 158 F (-20 to 70 C)
<b>CONNECTIONS</b>	
Side A - Connector 1	USB 3.0 A (MALE)
Side B - Connector 1	22 PIN SATA + POWER (FEMALE)
<b>WARRANTY &amp; SUPPORT</b>	
Product Warranty Period (Worldwide)	3-year limited warranty