



## ODC Series DC Output Module

File E29244

Users should thoroughly review the technical data before selecting a product part number. It is recommended that users also seek out the pertinent approvals files of the agencies/laboratories and review them to ensure the product meets the requirements for a given application.

### Features

- Industry standard package and pin-out.
- Color coded by function.
- 4000V rms optical isolation.
- High immunity to false operation.
- Series compatible.
- Output modules can be controlled from sinking or sourcing logic.
- Compatible with 2IO series mounting boards.

### Engineering Data

**Switch Form:** 1 Form A (SPST-NO)  
**Duty:** Continuous.  
**Operating Temperature:** -30°C to +80°C.  
**Storage Temperature:** -30°C to +100°C.  
**Potting Compound Flammability:** UL94V-0.  
**Approximate Weight:** 1.38 oz. (35g).

### Ordering Information

Typical Part Number > **ODC -5 A**

**1. Basic Series:** ODC = DC Output module — red case

**2. Input Voltage:** 5 = 5VDC  
 15 = 15VDC  
 24 = 24VDC

**3. Output:** Blank = 3A, 3-60VDC output\*\*  
 A = 1A, 3-250VDC output\*\*

\*\* Is not polarity sensitive.

Our authorized distributors are more likely to maintain the following items in stock for immediate delivery.

ODC-5  
 ODC-5A  
 ODC-15  
 ODC-15A  
 ODC-24

### Input Specifications

Parameter	Conditions	Units	ODC-5 ODC-5A			ODC-15 ODC15A			ODC-24 ODC-24A		
			Min.	Typ.	Max.	Min.	Typ.	Max.	Min.	Typ.	Max.
Control Voltage Range $V_{IN}$		VDC	3	5	8	9	15	18	18	24	32
Must Operate Voltage $V_{IN(OP)}$		VDC			3			9			18
Must release Voltage $V_{IN(REL)}$		VDC	1			1			1		
Maximum Input Current	@ $V_{IN}$ =Nominal	mADC		8 - 20			13 - 20			8 - 20	
Input Resistance $R_{IN}$		Ohms	Current Regulator								

PIN-3 must be positive with respect to PIN-4 for correct operation.

