

Now available in a 5 1/2" version. The added 1/2" length is for greater stability and cutting performance.

- > precision ground cutting edges without bevel for flush cutting the finest of wires e.g. in electronics and precision engineering
- > precisely shaped tips also cut adjacent wires from 1/64" (0.20 mm) diameter
- > opening spring and opening limiter user-friendly handle width
- > extremely smooth movement for minimum operator fatigue

78 03 140 / 78 03 140 ESD

Durable and stainless, made from INOX surgical steel, cutting edges hardened to 54 HRC

78 61 140 / 78 61 140 ESD

Heavy-duty, made from burnished special tool steel, cutting edges induction hardened (approx. 64 HRC)

78 03 140 ESD / 78 61 140 ESD

Allows electrostatic energy to discharge through the handles protecting components from electrostatic discharge



78 03 140



78 61 140 ESD



5 1/2" (140 mm) length: stronger and extremely versatile



For flush cutting, e.g. to shorten cable ties



Shear cut blade design for precise cutting

Product Number	Packaging	↔ Inch mm		Head	Handles	⊙ Ø Inch Ø mm	⊙ Ø Inch Ø mm	A Inch mm	B Inch mm	D Inch mm	⚖ lbs
78 03 140		5 1/2 140	▲	polished	multi-component grips	1/64 - 1/8 0.2 - 2.1	1/16 1.2	39/64 15.5	31/64 12.5	23/64 13.5	0.17
78 03 140 ESD		5 1/2 140	▲	polished	ESD multi-component grips	1/64 - 1/8 0.2 - 2.1	1/16 1.2	39/64 15.5	31/64 12.5	23/64 13.5	0.17
78 61 140		5 1/2 140	▲ ⚠		multi-component grips	1/64 - 1/8 0.2 - 2.1	1/16 1.2	39/64 15.5	31/64 12.5	23/64 13.5	0.17
78 61 140 ESD		5 1/2 140	▲ ⚠		ESD multi-component grips	1/64 - 1/8 0.2 - 2.1	1/16 1.2	39/64 15.5	31/64 12.5	23/64 13.5	0.17