


ITEM NO.	PART NUMBER	DESCRIPTION	QTY.	COMPONENT NOTES
1	50-00987	Connector, 4 pin M12 A-code plug, 12xL22mm, gold plated, molding style, solder cup, IP67, shielded	1	
2	50-00980	Connector, 4 pin M12 A-code socket, 12xL22mm, gold plated, molding style, solder cup, IP67, shielded	1	
3	30-01578	Wire, 4C TS, 22 AWG, UL20387, 300V, 105C, 60C oil, UV, 6 mm, shielded, VW-1, PVC, 80A, black	1	
4	24-00361	Overmold, M12 plug and jack, 90°	1	PVC, black
5	24-00349	Overmold, M12 plug and jack, 180°	1	PVC, black



**Notes:**  
Cable rated for 250 V, 4 A  
Temperature: -40 ~ 105 °C  
Oil resistant up to 60 °C  
Water resistant up to 75 °C  
UV resistant

IP67 waterproof rating when mated with corresponding (IP67) connector

Functionally equivalent components may be substituted

Wiring Diagram		
50-00987	wire color	50-00980
1	red	1
2	yellow	2
3	black	3
4	white	4
Shell	shield/drain	Shell

Revision: A	Date: 01/04/2022	Description: Initial release	Prepared: <b>MP</b> Digitally signed by MP Date: 2022.07.13 09:27:51 -07'00'	Notes: RoHS compliant	<b>TENSILITY</b> tel 1.541.323.3228 800 877.670.7118 fax 1.541.323.4202 web tensility.com
			Verified: <b>PB</b> Digitally signed by PB Date: 2022.07.13 13:40:34 -07'00'	Function test: no open, no short circuit, no intermittent	
			Dimensions are in millimeters. Tolerances: X: ± 0.5 mm X.X: ± 0.3 mm X.XX: ± 0.05 mm	Description: Cable, 10000 mm, 1.0 mm 4C 90° 50-00987 M12 plug to 1.0 mm 50-00980 M12 socket, 22 AWG, 30-01578 wire	Size: A Part number: 10-05084
					Scale: 1:1  Sheet 1 of 1

5 4 3 2 1