

at Serial Adapter (DB9 to DB25 F/M)

MODEL NUMBER: P100-000-R



Highlights

- Converts DB9 male serial connector to a DB25 male serial connector
- Fully shielded against EMI/RFI interference
- Gold Plated Connectors

System Requirements

- DB25F serial port on a PC or cable

Package Includes

- Serial Adapter Block DB9F to DB25M Gold Connectors

Description

Tripp Lite's serial adapter has gold plated connectors and will convert a DB9 male connector into a DB25 male connector. Lets a serial device with a DB9 connector attach to a PC with a DB25 port. PVC premold encapsulates individual conductors to ensure electrical isolation and relieve stress. 28 AWG stranded tinned copper conductors are individually insulated in polypropylene. This minimizes cross talk and ensures high-speed, error-free transmission. Clamshell retail packaging.

Features

- Connects a DB9 serial device to a DB25 cable or port
- Gold plated contacts and connectors for superior conductivity

Specifications

| OVERVIEW | |
|---------------------------------|----------------------|
| UPC Code | 037332011626 |
| PHYSICAL | |
| Color | Black |
| Shipping Dimensions (hwd / in.) | 5.50 x 4.50 x 1.25 |
| Shipping Dimensions (hwd / cm) | 13.97 x 11.43 x 3.18 |
| Shipping Weight (lbs.) | 0.22 |
| Shipping Weight (kg) | 0.10 |
| CONNECTIONS | |
| Side A - Connector 1 | DB9 (FEMALE) |



1000 Eaton Boulevard
Cleveland, OH 44122
United States

| | |
|-------------------------------------|---------------------------|
| Side B - Connector 1 | DB25 (MALE) |
| WARRANTY & SUPPORT | |
| Product Warranty Period (Worldwide) | Lifetime limited warranty |



© 2023 Eaton. All Rights Reserved.
Eaton is a registered trademark. All other trademarks
are the property of their respective owners.