

## Housing - HC-B 6-TFL-43/M2PG13,5S - 1679058

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)

Sleeve housing, for single locking latch, height: 44 mm, with screw connection, 2 x Pg13.5, lateral cable outlet



The figure shows the version with a lateral cable outlet



### Key commercial data

Packing unit	1 pc
Weight per Piece (excluding packing)	137.75 GRM
Custom tariff number	85389099
Country of origin	Germany

### Technical data

#### Dimensions

Height	44 mm
Width	43 mm
Length	60 mm
Wrench size, union nut	20 mm
External cable diameter	7.5 mm ... 12.5 mm

#### Ambient conditions

Degree of protection of housing (IP)	IP65
Ambient temperature (operation)	-40 °C ... 125 °C

#### General

Note	For contact inserts HC-B6, BB10, DD24, M
Design	B6
Housing type	Sleeve housings
Locking type	for single locking latch
No. of cable exits	2

# Housing - HC-B 6-TFL-43/M2PG13,5S - 1679058

## Technical data

### General

Cable exit	Lateral
Screw connection	With
Type of the screw connection	2x Pg13.5
Housing material	Aluminum die-cast
Housing surface material	Powder-coated, gray
Cable gland material	Nickel-plated brass
Cable seal material	NBR

## Classifications

### eCl@ss

eCl@ss 4.0	27140816
eCl@ss 4.1	27140816
eCl@ss 5.0	27143424
eCl@ss 5.1	27143424
eCl@ss 6.0	27143424
eCl@ss 7.0	27440209
eCl@ss 8.0	27440209

### ETIM

ETIM 2.0	EC000437
ETIM 3.0	EC000437
ETIM 4.0	EC000437
ETIM 5.0	EC000437

### UNSPSC

UNSPSC 6.01	31261502
UNSPSC 7.0901	31261502
UNSPSC 11	31261502
UNSPSC 12.01	31261502
UNSPSC 13.2	31261502

## Approvals

### Approvals

---

Approvals

GOST

## Housing - HC-B 6-TFL-43/M2PG13,5S - 1679058

### Approvals

---

Ex Approvals

---

Approvals submitted

---

### Approval details



### Drawings

Dimensioned drawing

