


SPECIFICATION CONTROL DRAWING

55PC0813

TITLE WIRE, RADIATION-CROSSLINKED, MODIFIED, ETFE-INSULATED, GENERAL PURPOSE, NORMAL AIRFRAME	Date 07-15-04	Revision D
---	------------------	---------------

This specification sheet forms a part of the latest issue of Raychem Specification 55PC.

CONDUCTOR - NICKEL-COATED COPPER
INSULATION - RADIATION-CROSSLINKED, MODIFIED ETFE



CONSTRUCTION DETAILS

PART NUMBER 1/	WIRE SIZE (AWG)	CONDUCTOR STRANDING (number x AWG)	CONDUCTOR DIAMETER (in.)			MAXIMUM RESISTANCE AT 20°C (ohms/1000ft.)	FINISHED WIRE DIAMETER (in.)			WEIGHT (lbs/1000 ft.)	
			LOWER SPEC LIMIT	TARGET VALUE	UPPER SPEC LIMIT		LOWER SPEC LIMIT	TARGET VALUE	UPPER SPEC LIMIT	TARGET VALUE	UPPER SPEC LIMIT
55PC0813-26-*	26	19 x 38	.0175	.0183	.0191	42.2	.0366	.0385	.0404	1.55	1.70
55PC0813-24-*	24	19 x 36	.0225	.0233	.0241	25.9	.0416	.0435	.0454	2.18	2.34
55PC0813-22-*	22	19 x 34	.0285	.0293	.0301	16.0	.0476	.0495	.0514	3.12	3.30
55PC0813-20-*	20	19 x 32	.0365	.0375	.0385	9.77	.0561	.0580	.0599	4.64	4.85
55PC0813-18-*	18	19 x 30	.0452	.0464	.0476	6.10	.0659	.0680	.0701	6.94	7.27
55PC0813-16-*	16	19 x 29	.0514	.0527	.0538	4.76	.0737	.0760	.0783	8.80	9.17
55PC0813-14-*	14	19 x 27	.0644	.0659	.0674	3.00	.0896	.0920	.0944	13.50	13.99
55PC0813-12-*	12	37 x 28	.0825	.0845	.0865	1.98	.1076	.1105	.1134	20.45	21.08
55PC0813-10-*	10	37 x 26	.1050	.1070	.1090	1.24	.1290	.1330	.1370	31.73	32.78
55PC0813-8-*	8	133 x 29	.158	.163	.169	.694	.188	.196	.203	56.8	59.9
55PC0813-6-*	6	133 x 27	.198	.205	.212	.436	.233	.242	.251	89.7	94.7
55PC0813-4-*	4	133 x 25	.250	.260	.268	.275	.300	.311	.322	146.	154.
55PC0813-2-*	2	665 x 30	.320	.330	.340	.177	.370	.383	.397	227.	240.
55PC0813-0-*	0	1045 x 30	.395	.415	.425	.113	.449	.466	.483	343.	366.
55PC0813-00-*	00	1330 x 30	.440	.462	.475	.089	.505	.525	.545	450.	481.

WIRE RATINGS AND ADDITIONAL REQUIREMENTS

<p>TEMPERATURE RATING: 200°C Maximum continuous conductor temperature</p> <p>VOLTAGE RATING: 600 volts (rms) at sea level</p> <p>COLOR: White preferred</p> <p>CROSSLINK VERIFICATION: 300 ± 3°C for 1 hour</p> <p>IDENTIFICATION AND COLOR STRIPING DURABILITY: 125 cycles (250 strokes) (minimum), 500 g weight</p>	<p>INSULATION ELONGATION AND TENSILE STRENGTH: Total Insulation, Elongation, 50% (minimum) Tensile Strength, 5000 lbf/in² (minimum)</p> <p>INSULATION FLAWS: Spark Test, 3.0 kV (rms) Impulse Dielectric Test, 8.0 kV (peak)</p> <p>INSULATION THICKNESS: .010 in. (nominal) total insulation</p>	<p>SHRINKAGE: 230 ± 3°C for 1 hour, 0.125 in. (maximum) in 12 in.</p> <p>VOLTAGE WITHSTAND TEST (Post Environmental): 2500 volts (rms)</p> <p>PART NUMBER: The "*" in the part numbers above shall be replaced by color code designators. 1/ Example: AWG 22, white: 55PC0813-22-9 AWG 22, white with black stripe: 55PC0813-22-90</p>
---	--	--

Users should evaluate the suitability of this product for their application. Specifications are subject to change without notice. Tyco Electronics also reserves the right to make changes in materials or processing, which do not affect compliance with any specification, without notification to Buyer.

1/ COLORS AND COLOR CODE DESIGNATORS SHALL BE IN ACCORDANCE WITH MIL-STD-681. OTHER CODES AND SUFFIXES MAY BE ADDED TO THE PART NUMBER, AS NECESSARY, TO CAPTURE ANY ADDITIONAL REQUIREMENTS IMPOSED BY THE PURCHASE ORDER.

DIMENSIONS ARE IN INCHES AND, UNLESS OTHERWISE DESIGNATED, ARE NOMINAL

THIS SPECIFICATION SHEET TAKES PRECEDENCE OVER DOCUMENTS REFERENCED HEREIN. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATION FOR BID.

