



KEY-B CONFIGURATION
P/N ATM06-08SB-CAP
INSERT COLOR: BLACK



KEY-C CONFIGURATION
P/N ATM06-08SC-CAP
INSERT COLOR: GREEN



KEY-D CONFIGURATION
P/N ATM06-08SD-CAP
INSERT COLOR: BROWN

REVISIONS					
REV	ECO	DESCRIPTION	DATE	BY	APPR
A1	-	RELEASE	26JUN15	JAH	
A2	-	REVISED COLOR AND IP RATING	20NOV2020	JAH	DH

NOTES: UNLESS OTHERWISE SPECIFIED

- MATERIAL: THERMOPLASTIC, HOUSING COLOR: GREY
INSERT COLOR: PER KEY CONFIGURATION
- RoHS COMPLIANT
- MOISTURE RESISTANCE: IP68 (1M OF WATER FOR
A PERIOD OF 24 HOURS , MATED CONDITION)
- TEMPERATURE RANGE: -55C~125C
- USE WITH CONNECTORS ATM06-08SX*
(X = A,B,C,D KEYS; * = MODIFICATIONS AND/OR COLORS)
- ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.

SEE KEY OPTIONS		PART NUMBER		DESCRIPTION		ITEM
QUANTITY						
MATERIALS LIST						
UNLESS OTHERWISE SPECIFIED:						
1) All dimensions are in metric (mm).						
2) Tolerances are as follows:						
1 PL DEC ±0.30						
2 PL DEC ±0.15						
3 PL DEC ±0.08						
3) Note reference = Fractions ±1/64 Angles ±1°						
SIGNATURES		DATE		Sine Systems - www.amphenol-sine.com 44724 Morley Drive Clinton Township, MI 48036		
DRAWN: J. HEAD		23JUN2015				
CHECKED:						
ENGINEER:						
APPROVAL:				PROTECTIVE CAP, 8 POSITION, ATM-SERIES		
MATERIAL SPECIFICATIONS:		CUSTOMER:		THIS DRAWING IS SUPPLIED FOR INFORMATION ONLY. DESIGN FEATURES, SPECIFICATIONS AND PERFORMANCE DATA SHOWN HEREON ARE THE PROPERTY OF THE AMPHENOL CORPORATION. NO RIGHTS OF REPRODUCTION ARE IMPLIED. ALL DIMENSIONS ARE SUBJECT TO NORMAL MANUFACTURING VARIATIONS.		
PROCESS SPECIFICATIONS:		SCALE: NONE		SIZE: B C-	DWG NO: ATM06-08SX-CAP	REVISION: A2
NEXT ASSY:		SHEET 1 OF 1				

TITLE: PROTECTIVE CAP, 8 POSITION, ATM-SERIES
DWG NO: ATM06-08SX-CAP
REV: A2
SH: 1
OF: 1