



- Notes
- ① The recommended clamp torque of ref. No. ③ : 3 to 4 N·m. LOCTITE 243, HENKEL JAPAN or equivalent is recommended to prevent from loosening.
 - ② The recommended clamp torque of ref. No. ③ : 0.2 to 0.3 N·m. LOCTITE 243, HENKEL JAPAN or equivalent is recommended to prevent from loosening.
 - ③ This products to be used with cable clamp JRT3WCC-*(73) ※ designate diameter of applicable cable.
 - ④ Rotation examples of ref. No. ⑤, ⑥ to ref. No. ⑦ is shown.
 - ⑤ The cable pull and twisting strength, waterproof tightness and other characteristics may differ depending on the cable structure. Please confirm before the use.

6	BRASS	NICKEL PLATING	12	STAINLESS STEEL	
5	NITRIL BUTADIENE RUBBER	(GRAY)	11	POLYACETAL	(WHITE)
4	PPS	UL94V-0 (BLACK)	10	NITRIL BUTADIENE RUBBER	(GRAY)
3	PPS	UL94V-0 (BLACK)	9	BRASS	NICKEL PLATING
2	COPPER ALLOY	SURFACE : GOLD PLATING 0.2µm MIN. UNDER : NICKEL PLATING 3µm MIN.	8	BRASS	NICKEL PLATING
1	BRASS	NICKEL PLATING	7	PHOSPHOR BRONZE	NICKEL PLATING

UNITS	SCALE	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	2 : 1	1	DIS-C-00003899	TY. SUZUKI	HY. KOBAYASHI	20200324
APPROVED : HY. KOBAYASHI		20180222	DRAWING NO.	EDC-114785-32-00		
CHECKED : HY. KOBAYASHI		20180222	PART NO.	RM15WTL P-4S(32)		
DESIGNED : HY. KISHI		20180222	CODE	CL109-1888-9-32		
DRAWN : MK. INOUE		20180208	NO.			