


REV.	DESCRIPTION	DATE	APPROVED
B	Engineering Update w/o Changes	02/23/04	M. C.
C	Typo Correction	04/06/05	M. C.
D	Removed P/Ns	02/27/15	J. C.





PART NO.	L	IL	W	IW	C/C	D	IH	F	H
470-015	.495 (12.6mm)	.455 (11.6mm)	.245 (6.2mm)	.205 (5.2mm)	.192 (4.9mm)	.028 (.71mm)	.015 (.38mm)	.000 (0.0mm)	.050 (1.3mm)
470-025							.025 (.64mm)	.010 (.25mm)	.060 (1.5mm)
470-035							.035 (.89mm)	.020 (.51mm)	.070 (1.8mm)
470-045							.045 (.71mm)	.030 (.76mm)	.080 (2.0mm)
471-015	.495 (12.6mm)	.455 (11.6mm)	.245 (6.2mm)	.205 (5.2mm)	.192 (4.9mm)	.050 (1.3mm)	.015 (.38mm)	.000 (0.0mm)	.050 (1.3mm)
471-025							.025 (.64mm)	.010 (.25mm)	.060 (1.5mm)
471-035							.035 (.89mm)	.020 (.51mm)	.070 (1.8mm)
471-045							.045 (.71mm)	.030 (.76mm)	.080 (2.0mm)
473-015	.825 (21.0mm)	.775 (19.7mm)	.425 (10.8mm)	.375 (9.5mm)	.486 (12.3mm)	.060 (1.5mm)	.015 (.38mm)	.000 (0.0mm)	.075 (1.9mm)
474-045	.825 (21.0mm)	.775 (19.7mm)	.425 (10.8mm)	.375 (9.5mm)	.486 (12.3mm)	.110 (2.8mm)	.045 (.71mm)	.030 (.76mm)	.105 (2.7mm)

2. MATERIAL: NYLON 6/6, 94V-2, WHITE. BIVAR MATERIAL CODE 04-WE.

BASF ULTRAMID NYLON 6/6 A3K WHITE.

1. GENERAL SPECIFICATIONS: BIVAR MOLDED COMPONENT SPECIFICATION BV00-E101.

STANDARD TOLERANCE (UNLESS OTHERWISE SPECIFIED)		 BIVAR [®] 4 THOMAS, IRVINE, CA. 92618 TEL: (949) 951-8808 FAX: (949) 951-3974			
DECIMALS	ANGULAR				
.X ±.1	X° ± 1°	 TITLE: CRYSTAL MOUNT SERIES			
.XX ±.01					
.XXX ±.005		DESIGNED: Michael Chen	DATE: 03/10/03	PART NO: 47X-XXX	REVISION: D
		CHECKED: D. Green	DATE: 03/10/03		CAGE CODE: 32559
CAD GENERATED DOCUMENT, DO NOT MEASURE DRAWING.					