

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

2008

© COPYRIGHT 2008

ALL RIGHTS RESERVED.

LOC
AL DIST
2

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	Y4	REVISED PER ECN-21-128636	02DEC2021	WLS	VS

1 OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

Terminal Conductor: FLK-Cable
Conductor: F-Crimp
Insulation: F-Crimp

Cross-section in mm²

	Single connection	0.50	0.75	1.00	1.50	2.00	2.50	3.00	4.00	6.00
0.50	X	X	X	X	X					
0.75	X	X	X	X						
1.00	X	X	X	X						
1.50	X	X								
2.00										
2.50										
3.00										
4.00										
6.00										

0- -1,2,3,4,6,7 as shown

Wire size: 0.5-2.0 mm²

0- -5 as shown

1	OBSOLETE	Bright	Brass	-925660-7-
		Gold over Ni	Phosphor Bronze	925660-6
	OBSOLETE	Pre-tin plated	Steel	-925660-5-
		Bright	Phosphor Bronze	925660-4
		Silver	Phosphor Bronze	925660-3
		Pre-tin plated	Phosphor Bronze	925660-2
		Pre-tin plated	Brass	925660-1
		Finish	Material	Part no.

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:
mm

MATERIAL See table

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC	±0.2
1 PLC	±0.2
2 PLC	±0.2
3 PLC	±
4 PLC	±
ANGLES	±1° 30'
FINISH	See table

DWN J. Salo 12NOV2008

CHK R. Sole 12NOV2008

APVD P.F.Grassano 12NOV2008

PRODUCT SPEC

108-1032

APPLICATION SPEC

114-1007

WEIGHT -

CUSTOMER DRAWING

12NOV2008

12NOV2008

12NOV2008

NAME

108-1032

114-1007

-

NAME

108-1032

114-1007

-

-

TE Connectivity

.140 DIA PIN

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A3	-	925660	

SCALE	2:1	SHEET	1 OF 1	REV	Y4
-------	-----	-------	--------	-----	----

SCALE 2:1

SHEET 1 OF 1

REV Y4

1470-19 (3/11)