



DETAIL A



Recommended PCB Layout  
(Top View)



**Materials and Finish**

Housing Material:  
 high temp. thermoplastic,  
 (reflow process compatible)  
 UL 94V-0 rated, black color

Design meets UL 1863 Sec. 8  
 Electrical Probe and Sec. 20  
 Child Finger test requirements

Contact Material: phosphor bronze

Contact Plating Options:  
 Standard: 0.0001" Nickel  
 Plating, Selective Plating  
 Gold Flash on Contact  
 Area, Tin on Termination End

50: 0.0001" Nickel Plating,  
 Selective Plating 0.000050"  
 Gold on Contact Area to  
 Comply with FCC Requirements  
 Under No. 47 C.F.R. Part 68,  
 Subpart F, Tin on Termination End

**Electrical Characteristics**

Current Rating: 1.0 Amps  
 Current Voltage: 125V DC  
 Insulation Resistance:  
 500 Megohms min.

Dielectric Withstanding Voltage:  
 1000V rms, 60Hz

Contact Resistance:  
 20 milliohms max.

Durability Rating:  
 1000 mating cycles min.

Operating Temperature:  
 -40°C to +85°C

Part Number	Gold Plating	Packaging
GMX-SMT2-N-66	Flash	Bulk
GMX-SMT2-N-66-50	50u"	Bulk
GMX-SMT2-N-66-TR	Flash	Tape & Reel
GMX-SMT2-N-66-50TR	50u"	Tape & Reel

Tolerances
X.X ± 0.38
X.XX ± 0.25
Unless Stated Otherwise



REV.	DATE	DESCRIPTION	REV. BY	CHK. BY	DRAWN BY	DATE
A1	06/30/05	New Drawing	R. Aguirre	H. MA	R. Aguirre	05/23/05
A2	04/27/10	ECO #10-020	S. Vien	H. MA		
A3	12/08/10	ECO #10-088	S. Vien	H. MA		
A4	08/20/12	ECO #12-027	S. Vien	P. DalCanto	UNITS	mm
A5	11/06/13	ECO #13-084	W. Cook	H. MA		
A6	05/28/15	ECO #15-001	H. MA	C. Furumasu		

**GMX-SMT2-N-66**

Right Angle Modular Jack, RoHS Compliant

6 position, 6 contacts, Surface Mount

