
Handy, compact and sturdy Extremely robust design





- > two-stage ratchet drive for easy cutting
- > less physical effort due to very high transmission ratio
- > fixed handle with support area for laying down the pliers when cutting
- > locking mechanism for transporting with safely closed handles
- > high-grade special tool steel; forged, multi stage oil-hardened









95 32 340 SR US

						Cutting capacities		
Product Number	Packaging	←→ Inch mm		Tool	Handles	AAC (All Aluminum Conductor) Ø Inch Ø mm	ACSR (Aluminum Conductor Steel Reinforced) kcmil	∆ ∆ lbs
95 32 340 SR US	X	13 25/64 340	* MM EI	burnished	multi-component grips	1 1/4 32	795	2.87

Bowden Cable Cutter

95 6



- > for Bowden cables and soft wire rope up to 1/8" (3.0 mm) dia. (also V2A)
- > smooth and clean cutting due to special shape of the cutting edges
- > sickle shape cutting edges surround the material and prevent the wire rope fanning out
- > minimal handforce required due to very high transmission ratio
- > with opening spring and locking lever
- > induction hardened cutting edges
- > high-grade special tool steel; forged, multi stage oil-hardened



							Cutting capacities	
		←→						
		Inch					Ø Inch	$\Delta \Delta$
Product Number	Packaging	mm		Shears	Head	Handles	Ø mm	lbs
0F 61 1F0 HC	V	6		black atramentized	polished	plastic coated	1/8	0.48
95 61 150 US	٨	150	DIACK ALIAINEIILIZEO	polistieu	piastic coated	3	0.48	