

Cable glands
VG M50 - MS 68

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com



Screwed joints that comply with the high demands of class of protection IP 68

General ordering data

Order No.	1772260000
Type	VG M50 - MS 68
Version	Cable gland, Brass, nickel-plated, External thread: M 50
GTIN (EAN)	4032248129911
Qty.	15 pc(s).

**Cable glands
VG M50 - MS 68**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data

Dimensions and weights

Length	57 mm	Net weight	280.2 g
--------	-------	------------	---------

General information

AF size 1	50 mm	AF size 2	55 mm
Clamp insert	Polyamide	Clamping range, max.	32 mm
Clamping range, min.	22 mm	External thread	M 50
Length of thread	9 mm	Material	Brass, nickel-plated
Operating temperature range, max.	100 °C	Operating temperature range, min.	-40 °C
Pitch of thread	1.5	Protection degree with GWDR	IP 68 - 5 bar
Torque for cap nut, max.	41.5 Nm	Torque for cap nut, min.	38.5 Nm
Torque for connecting adapter, max.	20 Nm	Torque for connecting adapter, min.	16 Nm

Classifications

ETIM 3.0	EC000441	eClass 6.2	27-14-91-09
eClass 7.1	27-14-91-09		

Approvals

Approvals



ROHS	Conform
------	---------