## 3 METERS LENGTH



Connector A 132279 SMA Jack Straight Brass Gold + Heatshrink 50 Ohm RG-178 Continuity/Hi-Pot Connector B 172313 N-Type Jack Straight Bulkhead - Rear Mount Brass White Bronze + Heatshrink

## Assembly & Label Notes

Assembly label to be placed ~ 2" from end of connector A and/ or heat shrink Assembly shall be built with SN96.5 LEAD FREE solder. See Routing Notes for additional assembly & testing instructions.

|                          | Connector A      |                  |   | Cable  |                   |                             | Connector B         |  |  |
|--------------------------|------------------|------------------|---|--|-------------------|-----------------------------|---------------------|--|--|
| Part #                   | #: 13            | 2279             |   | Part #:  | RG-178            | Part #:                     | 172313              |  |  |
| Desci                    | ription: SN      | MA JK RG178 RG   | G196 50O  | Description:   | RG-178 - ST 0.072 | Description:                | N-Type BHD JK RG    | 178 RG196 500  |  |
| Type:                    | : SN             | AN               |   | Dielectric:  | ST                | Туре:                       | N-Type              |  |  |
| Gend                     | der: Ja          | ck               |   | Shielding:   | Braid             | Gender:                     | Jack                |  |  |
| Body                     | / Type: Str      | raight           |   | Diameter:  | 0.072             | Body Type:                  | Straight            |  |  |
| Conta                    | act Type: So     | older            |   | Impedance:   | 50 Ohm            | Contact Type:               | Solder              |  |  |
| Polar                    | rity: Sta        | andard           |   | Sheathing:   | None              | Polarity:                   | Standard            |  |  |
| Imped                    | dance: 50        | Ohm              |   | Testing:   | Continuity Hi-Pot | Impedance:                  | 50 Ohm              |  |  |
| Moun                     | nting: Ca        | able             |   | Length:  | 3 Meters          | Mounting:                   | Bulkhead - Rear Mo  | unt  |  |
| Body                     | / Material: Bra  | ass              |   | -  |                   | Body Material:              | Brass               |  |  |
| -                        | / Finish: Go     | bld              |   |  |                   | Body Finish:                | White Bronze        |  |  |
| IP Rai                   |                  | one              |   |  |                   | IP Rating:                  | None                |  |  |
| Conta                    | act Material: Be | eryllium Copper  |   |  |                   | Contact Material:           | Phosphor Bronze     |  |  |
| Conta                    | act Finish: Go   | , ,,             |   |  |                   | Contact Finish:             | Gold                |  |  |
| Max.                     | Freq.: 12        | .4 GHz           |   |  |                   | Max. Freq.:                 | 11 GHz              |  |  |
| Booti                    | •                | MA Jack Straight |   |  |                   | Booting:                    | N-Type Jack Straigh | t BHD  |  |
|                          |                  |                  |   |  |                   | Clocking:                   | 0°                  |  |  |
| THIS DRAWING MAY CONTAIN |                  |                  |   | Title:   |                   |                             | UNLESS SPECIFIED    |  |  |
| FOR ANY PURPO            |                  |                  | FOR ANY PURPOSE DETRIMENT<br>INC. IT MAY NOT BE REPRODUC                                    | ETARY INFORMATION AND MUST NOT BE USED<br>Y PURPOSE DETRIMENTAL TO CUSTOM CABLE<br>MAY NOT BE REPRODUCED OR TRANSCRIBED<br>FORM WITHOUT THE WRITTEN CONSENT OF |                   | SMA-ST-JK/N-ST-JK G178 3M   |                     | TOLERANCE:<br>0-18 inches +/- 1/2"<br>over 18" +/- 2%<br>ASSEMBLY: |  |
|                          |                  |                  | CUSTOM CABLE INC. ACCEPTANCE OF THIS DRAWING<br>ESTABLISHES AND AGREEMENT OF THE FOREGOING. |  | IG Part No:       | Part No:<br>Q-2T01Z0001003M |                     | CENTER LABEL IF LENGT<br>IS LESS THAN 12 INCHES                    |  |



## **RoHS 2015/863 Compliance Statement**

According to the manufacture of all the component parts contained in this assembly, this product has been determined to be RoHS Compliant with RoHS Directive 2011/65/EU and as amended by Directive 2015/863, and without material exceptions (RoHS3 Complaint).

For the individual component RoHS certificates used in this assembly, please contact Amphenol Custom Cable.

The RoHS Compliance of any product so designated is based upon evidence from the producer (manufacturers') that the component parts comply with the RoHS Directive. Amphenol Custom Cable has taken all reasonable steps to confirm that the OEM (Manufacturer) of the components used in this assembly have provided evidence regarding the absence of the restricted substances to support the manufacturer's claim of compliance.

To the best of our knowledge and with due diligence, we certify that the product listed herein complies with the RoHS requirements.

Date: 10/3/2023

Part Number: Q-2T01Z0001003M

Manufacturer: Amphenol Custom Cable

Description: SMA-ST-JK/N-ST-JK G178 3M

This information is valid as of the date indicated for the item (part number) listed.

**Director of Quality Assurance** 

Janice Frank