

Relay connectors - ST-REL4-HW 24/21-21 - 2823447

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Relay connector, equipped with Hengstler miniature round relay, contacts (AgCdO+Au): small to large loads, 2 PDT, input voltage 24 V AC, with light indicator, can be plugged on basic termination blocks

The illustration shows version ST-REL 4-HG 24/21-21



Key commercial data

| | |
|--------------------------------------|---|
| Packing unit | 1 pc |
| GTIN |  4 017918 077419 |
| Weight per Piece (excluding packing) | 72.67 GRM |
| Custom tariff number | 85364190 |
| Country of origin | Germany |

Technical data

Dimensions

| | |
|--------|---------|
| Width | 27 mm |
| Height | 33 mm |
| Depth | 66.5 mm |

Ambient conditions

| | |
|---|------------------|
| Ambient temperature (operation) | -20 °C ... 60 °C |
| Ambient temperature (storage/transport) | -20 °C ... 70 °C |

Coil side

| | |
|---|--------------------------|
| Nominal input voltage U_N | 24 V AC |
| Input voltage range in reference to U_N | 0.8 ... 1.1 |
| Typical input current at U_N | 75 mA |
| Typical response time | 4 ms ... 15 ms (with AC) |

Relay connectors - ST-REL4-HW 24/21-21 - 2823447

Technical data

Coil side

| | |
|----------------------------|---|
| Typical release time range | 4 ms ... 15 ms (with AC) |
| Operating voltage display | Yes |
| Protective circuit | Damping diode, polarity protection Damping diode, polarity protection diode |

Contact side

| | |
|---------------------------------------|-------------------------|
| Contact type | Single contact, 2-PDT |
| Contact material | AgCdO, hard gold-plated |
| Maximum switching voltage | 250 V AC/DC |
| Maximum inrush current | 6 A |
| Limiting continuous current | 6 A |
| Interrupting rating (ohmic load) max. | 120 W (at 24 V DC) |
| | 180 W (at 48 V DC) |
| | 105 W (at 60 V DC) |
| | 60 W (at 110 V DC) |
| | 90 W (at 220 V DC) |
| | 1250 VA (for 250 V AC) |

General

| | |
|--|-----------------------------------|
| Test voltage relay winding/relay contact | 2 kV AC (50 Hz, 1 min.) |
| Test voltage PDT/PDT | 2.5 kV AC (50 Hz, 1 min.) |
| Operating mode | 100% operating factor |
| Mechanical service life | Approx. 10 ⁷ cycles |
| Standards/regulations | DIN VDE 0110b, Gr. C for 250 V DC |
| | DIN VDE 0160 (in relevant parts) |

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.0 | 27371104 |
| eCl@ss 4.1 | 27371104 |
| eCl@ss 5.0 | 27371001 |
| eCl@ss 5.1 | 27371001 |
| eCl@ss 6.0 | 27371001 |
| eCl@ss 7.0 | 27371001 |
| eCl@ss 8.0 | 27371001 |

ETIM

| | |
|----------|----------|
| ETIM 2.0 | EC000196 |
|----------|----------|

Relay connectors - ST-REL4-HW 24/21-21 - 2823447

Classifications

ETIM

| | |
|----------|----------|
| ETIM 3.0 | EC000196 |
| ETIM 4.0 | EC000196 |
| ETIM 5.0 | EC000196 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 30211916 |
| UNSPSC 7.0901 | 39121515 |
| UNSPSC 11 | 39121515 |
| UNSPSC 12.01 | 39121515 |
| UNSPSC 13.2 | 39121515 |

Approvals

Approvals

Approvals

GOST / GOST

Ex Approvals

Approvals submitted

Approval details



Drawings

Relay connectors - ST-REL4-HW 24/21-21 - 2823447

Circuit diagram

