Product data sheet

Specifications



Limit switch lever, 9007, arm t+ft +options

9007B19

Main

| Wall | |
|-----------------------------|---|
| Range of product | 9007 |
| Series name | Severe duty |
| Product or component type | Limit switch lever |
| Device short name | 9007T/FT |
| Associated head | 9007AS9 9007NS9 9007CS9 9007T10S9 9007BS9 9007T5S9 |
| Associated complete product | 9007FT 9007T 9007CS9 |
| Movement of operating head | Rotary |
| Type of operator | Cast zinc spring return roller lever length: 127.00 mm - offset: - convertible roller |
| Type of roller | 1 steel outside roller (convertible) diameter: 19.05 mm - width: 6.35 mm |
| Type of approach | Lateral approach |
| Positive opening | Without |
| Complementary | |

Switch actuationBy 30° camProduct weight0.05 kg

Environment

| Ambient air temperature for operation | -2385 °C |
|---------------------------------------|----------------------|
| Ambient air temperature for storage | -2385 °C |
| Environmental characteristic | Standard environment |

Packing Units

| Unit Type of Package 1 | PCE |
|------------------------------|--------|
| Number of Units in Package 1 | 1 |
| Package 1 Height | 1.5 cm |

| Package 1 Width | 10.2 cm |
|------------------------------|----------|
| Package 1 Length | 20.3 cm |
| Package 1 Weight | 99.8 g |
| Unit Type of Package 2 | S01 |
| Number of Units in Package 2 | 25 |
| Package 2 Height | 15.0 cm |
| Package 2 Width | 15.0 cm |
| Package 2 Length | 40.0 cm |
| Package 2 Weight | 2.725 kg |

Offer Sustainability

| REACh Regulation | REACh Declaration |
|---------------------------|--|
| EU RoHS Directive | Not applicable, out of EU RoHS legal scope |
| Environmental Disclosure | Product Environmental Profile |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |

Contractual warranty

Warranty

18 months

Recommended replacement(s)