


**NEW!**  
Two & Three  
Section Models

# MMIC REFLECTIONLESS FILTERS

50Ω DC to 21 GHz

## The Big Deal

- High Stopband rejection, up to 50 dB
- Patented design terminates stopband signals
- Pass band cut-off up to 11 GHz
- Stop band up to 26 GHz
- Excellent repeatability through IPD\* process



**X-Series**

Available in Low Pass  
& High Pass designs

## Product Overview

Mini-Circuits' **X-Series** of reflectionless filters now includes 2- and 3-section models, giving you ultra-high rejection in the stopband – up to 50 dB! Reflectionless filters employ a patented filter topology which absorbs and terminates stopband signals internally rather than reflecting them back to the source. This new capability enables unique applications for filter circuits beyond those suited to traditional approaches. Traditional filters are reflective in the stopband, sending signals back to the source at 100% power. These reflections interact with neighboring components and often result in intermodulation and other interferences. By eliminating stopband reflections, reflectionless filters can readily be paired with sensitive devices and used in applications that otherwise require circuits such as isolation amplifiers or attenuators.

### Key Features

### Advantages

|   |   |
|---|---|
| Easy integration with sensitive reflective components, e.g. mixers, multipliers | Reflectionless filters absorb unwanted signals falling in filter stopband, preventing reflections back to the source. This reduces generation of additional unwanted signals without the need for extra components like attenuators, improving system dynamic range and saving board space. |
| High stopband rejection, up to 50 dB  | Ideal for applications where suppression of strong spurious signals and intermodulation products is needed.   |
| Enables stable integration of wideband amplifiers                               | Because reflectionless filters maintain good impedance in the stopband; they can be integrated with high gain, wideband amplifiers without the risk of creating instabilities in these out of band regions.   |
| Cascadable  | Reflectionless filters can be cascaded in multiple sections to provide sharper and higher attenuation, while also preventing any standing waves that could affect passband signals. Low & highpass filters can be cascaded to realize bandpass filters.                                     |
| Excellent power handling in a tiny surface mount device up to 7W in passband    | High power handling extends the usability of these filters to the transmit path for inter-stage filtering.  |
| Small size, 3x3mm/ 4x4 mm/ 5x5mm QFN  | Allows replacement of filter/attenuator pairs with a single reflectionless filter, saving board space.  |
| Excellent repeatability of RF performance                                       | Through semiconductor IPD process, X-series filters are inherently repeatable for large volume production.  |
| Excellent stability over temperature  | With ±0.3 dB variation over temperature ideal for use in wide temperature range applications without the need for additional temperature compensation.  |
| Operating temperature up to 105°C   | Suitable for operation close to high power components.  |

\*IPD – Integrated Passive Device, is a GaAs semiconductor process



# Reflectionless High Pass Filter

## XHF-143M+

50Ω 13900 to 19000 MHz

### Features

- Match to 50Ω in the stop band, eliminates undesired reflections
- Cascadable
- Good stopband rejection, 39 dB typ.
- Temperature stable, up to 105°C
- Small size, 3 x 3 mm
- Protected by US Patents 8,392,495; 9,705,467, additional patent pending
- Protected by China Patent 201080014266.1
- Protected by Taiwan Patent I581494



Generic photo used for illustration purposes only

CASE STYLE: DQ1225

### +RoHS Compliant

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications

### Applications

- Fixed Satellite
- Mobile
- Space research





Available Tape and Reel at no extra cost

| Reel Size | Devices/Reel                      |
|-----------|-----------------------------------|
| 7"        | 20, 50, 100, 200, 500, 1000, 2000 |

### General Description

Mini-Circuits' XHF-143M+ two-section reflectionless filter employs a novel filter topology which absorbs and terminates stop band signals internally rather than reflecting them back to the source. This new capability enables unique applications for filter circuits beyond those suited to traditional approaches. Traditional filters are reflective in the stop band, sending signals back to the source at 100% of the power level. These reflections interact with neighboring components and often result in inter-modulation and other interferences. Reflectionless filters eliminate stop band reflections, allowing them to be paired with sensitive devices and used in applications that otherwise require circuits such as isolation amplifiers or attenuators.

### simplified schematic and pad description



| Function            | Pad Number | Description            |
|---------------------|------------|------------------------|
| RF-IN               | 3          | RF Input Pad           |
| RF-OUT              | 7          | RF Output Pad          |
| GND                 | 2,4,6,8    | Connected to ground    |
| NC (GND Externally) | 1, 5,9-12  | No internal connection |



Electrical Specifications<sup>1</sup> at 25°C

| Parameter        | F#                | Frequency (MHz) | Min.          | Typ. | Max. | Unit |
|------------------|-------------------|-----------------|---------------|------|------|------|
| <b>Stop Band</b> | Rejection         | DC - F'         | DC - 7000     | 24   | 39   | —    |
|                  |                   | F' - F1         | 7000 - 9000   | 21   | 30   | —    |
|                  | Frequency Cut-off | F2              | 11200         | —    | 3.2  | —    |
|                  | VSWR              | DC - F'         | DC - 7000     | —    | 1.2  | —    |
|                  | F' - F1           | 7000 - 9000     | —             | 1.5  | —    | :1   |
| <b>Pass Band</b> | Insertion Loss    | F3 - F4         | 13900 - 15000 | —    | 1.1  | 1.8  |
|                  |                   | F4 - F5         | 15000 - 19000 | —    | 1.0  | 2.9  |
|                  | VSWR              | F3 - F4         | 13900 - 15000 | —    | 1.2  | —    |
|                  |                   | F4 - F5         | 15000 - 19000 | —    | 1.6  | —    |

<sup>1</sup> Measured on Mini-Circuits Characterization Test Board TB-967-143M+

Absolute Maximum Ratings<sup>4</sup>


| Parameter                                     | Ratings         |
|---|-----------------|
| Operating Temperature                         | -55°C to +105°C |
| Storage Temperature                           | -65°C to +150°C |
| RF Power Input, Passband (F3-F5) <sup>2</sup> | 1W at 25°C      |
| RF Power Input, Stopband (DC-F3) <sup>3</sup> | 1.25W at 25°C   |

<sup>2</sup> Passband rating derates linearly to 0.5W at 105°C ambient

<sup>3</sup> Stopband rating derates linearly to 0.63W at 105°C ambient

<sup>4</sup> Permanent damage may occur if any of these limits are exceeded.

SPECIFICATION DEFINITION





ESD rating


Human body model (HBM): Class 2(Pass 2000V) in accordance with ANSI/ESD 5.1-2001

Typical Performance Data at 25°C

| Frequency (GHz) | Insertion Loss (dB) | VSWR (:1) |
|-----------------|---------------------|-----------|
| 0.01            | 62.78               | 1.14      |
| 0.05            | 67.70               | 1.14      |
| 0.1             | 63.23               | 1.14      |
| 0.5             | 42.98               | 1.14      |
| 1.0             | 32.85               | 1.14      |
| 3.0             | 31.48               | 1.25      |
| 5.0             | 36.41               | 1.34      |
| 7.0             | 35.57               | 1.53      |
| 8.0             | 26.72               | 1.85      |
| 11.0            | 3.62                | 1.74      |
| 13.9            | 1.20                | 1.24      |
| 15.0            | 1.01                | 1.14      |
| 17.0            | 0.94                | 1.16      |
| 18.0            | 0.92                | 1.56      |
| 19.0            | 0.77                | 1.57      |
| 20.0            | 0.48                | 1.30      |
| 21.0            | 0.65                | 1.36      |
| 22.0            | 1.42                | 2.31      |
| 23.0            | 2.43                | 3.21      |
| 24.0            | 2.85                | 3.98      |
| 25.0            | 1.99                | 2.67      |
| 26.0            | 3.61                | 2.32      |



**Product Marking**



**Additional Detailed Technical Information**


additional information is available on our dash board. To access this information [click here](#)

|   |  |
|---|--|
| <b>Performance Data</b>   | Data Table   |
|   | Swept Graphs   |
|   | S-Parameter (S2P Files) Data Set (.zip file)                     |
| <b>Case Style</b>   | DQ1225 Plastic package, exposed paddle<br>lead finish: matte-tin |
| <b>Tape &amp; Reel</b><br>Standard quantities available on reel | F66<br>7" reels with 20, 50, 100, 200, 500 or 1K devices         |
| <b>Suggested Layout for PCB Design</b>                          | PL-590   |
| <b>Evaluation Board</b>   | TB-967-143M+   |
| <b>Environmental Ratings</b>                                    | ENV82  |

**ESD Rating**

Human Body Model (HBM): Class 2 (Pass 2000V) in accordance with ANSI/ESD STM 5.1 - 2001

**MSL Test Flow Chart**




**Additional Notes**

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
- C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at [www.minicircuits.com/MCLStore/terms.jsp](http://www.minicircuits.com/MCLStore/terms.jsp)

## Application Circuit Example

Pairing mixers with reflectionless filters to improve system dynamic range



Test block diagram: IF output reflection spectrum with single input frequency




Figure 1. IF output reflection spectrum without filter




Figure 2. IF output reflection spectrum with conventional filter

An application circuit was assembled to measure the IF reflection spectrum at the output of a mixer when the mixer was paired with a conventional filter versus a reflectionless filter.

While the conventional filter reduces the reflections present when the mixer is used alone (no filter), the reflectionless filter virtually eliminates those reflections altogether.

The reflected signal at marker 1 in the figures above exhibits a reduction of more than 20 dB from -28.7 dBm to -50.3 dBm when the reflectionless filter is used as compared to the conventional filter, thus eliminating unwanted spurious mixing products and improving system dynamic range.

For more information, refer to application note [AN-75-007](#)




Figure 3. IF output reflection spectrum with reflectionless filter

### Additional Notes

- Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- Electrical specifications and performance data contained in this specification document are based on Mini-Circuits' applicable established test performance criteria and measurement instructions.
- The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at [www.minicircuits.com/MCLStore/terms.jsp](http://www.minicircuits.com/MCLStore/terms.jsp)