

Eagle Eyes - AIML

6th Generation Intel® Core™ U Series Processor Fanless Box Computer, 2x RJ45 GbE



Models shown with Optional Antennas Kit

Features

- Wi-Fi and Wireless Communications: 4G, WLAN, GPS, GSM/GPRS, and Bluetooth
- 6th Gen Intel® platform (formerly Skylake), Core™ U Series processor
- Intelligent eKit with AI Function to monitor system status via the DDM
- Special Power Design:
 - * Wide voltage 9 - 36V DC input
 - * RVP / OVP / UVP / OCP support
 - * Surge protection: 80V/1ms
 - * Power ignition control
- Easy Expansion and Installation:
 - * Easy system upgrade capability
 - * On / Off power switch with status LED
 - * Remote on / off capabilities
 - * Easily replaceable RTC battery
 - * Two Mini PCIe interfaces
 - * Two SIM Push-Push sockets



Specifications

System

CPU	6th Gen Intel® Core™ (formerly Skylake U Series) i3-6100U (2/4 Cores, 2.3 GHz, 3M Cache, 15W TDP)
Memory	One SO-DIMM DDR4 2133/2400 (32GB Max)
Graphics	Intel® HD Graphics 520
BIOS	AMI 128Mbit SPI BIOS
AI Controller (AIC)	AI for system monitoring and predictive analysis Runtime: 10 – 65535 seconds Powerup: 120-65535 seconds
Watchdog Timer	

Power

DC Input	9 – 36V
Surge Protection	200V/1ms
Power in Protection	Reverse-Voltage, Over-Voltage, Under-Voltage, and Over-Current
Remote Ignition	One ATX power on/off switch, 5-pin terminal block including 3-pin remote control & 2-pin ignition signals (pitch 3.81mm)
Power Mode	AT/ATX (BIOS setting)

External I/O

Video Ports / Resolution	Two DP / 4096x2304@60Hz One VGA / 1920x1200@60Hz
Video Ports	Two DP + one VGA
Ethernet	Two RJ45 GbE (one Intel® i219 + one Intel® i210) / Wake-on LAN and PXE/ i219 supports iAMT 11.0
USB 3.0/2.0	Four USB 3.0 ports via native XHCI controller (0.9A each port)
COM	One RS-232/422/485 (auto flow control) and three RS-232 ports
Wi-Fi / Cellular Communication	Supports Wi-Fi/LTE modules via two Mini PCIe interfaces
Digital I/O	16-bit programmable DIO
Audio	ALC892 HD audio codec, Mic-in/Line-out
SIM Push-Push/USIM Sockets	Two SIM Push-Push sockets – SIM supports 2G USIM supports 3 & 4G

Optional

Wireless Module

Wi-Fi Module	Bointec DPE109A, WLAN 802.11abgn/AC2T2R with BT4.2 mini-PCIe half-size card support
LTE Module	Customer choice based on regional requirements

Cable & Connectors

CBL-S01	One SATA (Data + Power) cable
TBP5-S03	One 3-Pin, pitch 5.0 mm Female Terminal Block Plug for DC input
TBP3-S05	One 5-Pin, pitch 3.81 mm Female Terminal Block Plug for remote connector
TBP3-D20	One 2x10-Pin, pitch 2.54 mm Female Terminal Block Plug for DIO connector

Storage

Internal Drive Bay	One internal SATA port for 2.5" SSD
M.2 Connector	One M.2 M Key 2242 (1 – PCIe or 1 – SATA)

Mechanical

Dimensions (WxDxH)	161(W) mm x 130(D) mm x 68.1(H) mm (6.34" x 5.12" x 2.68")
Weight (net/gross)	1.7kg
Table or Wall Mount	Four Rubber anti-slide pads included (Wall mount optional)
Construction	Aluminum and metal chassis with fanless design
Battery	Easily replaceable RTC battery
Dynamic Display Module (DDM)	0.96" LCM works with AIC to display system status

Environment

Operating Temperature	Standard: -20°C ~+50°C (-47°F~+122°F), supports 35W TDP CPU Extended temperature: -25°C ~+70°C (-13°F ~+158°F)
Storage Temperature	-40°C - +85°C (-40°F - +185°F)
Relative Humidity	95% @ -40°C (+104°F), non-condensing
Vibration During Operation	5Gms with SSD (IEC60068-2-64: random 5-500Hz)
Shock During Operation	50Gms with SSD (IEC60068-2-27: Half Sine, 11ms duration)

Other

USB 2.0 Dongle	One Internal USB 2.0 for dongle security key
Antenna	Four Antenna openings
LED	Power status, SSD status, and I/O status

Certifications

EMC	CE/FCC Class A
Safety Certification(s)	CB

OS Support

Windows	Windows 10 IoT 64-bit
Linux	Linux

Mounting Kits

WBK-AIH	Wall mount bracket x 2 with Six (6) M3x6 screws
----------------	---

TPM

	Infineon OPTIGA™ TPM SLB 9665 TPM 2.0
--	---------------------------------------


Antenna Kits

20140-000031-A.0	Wi-Fi, one mini-PCIe half to full size adapter bracket, two antennas supporting IPX/MHF to SMA_JR 300 MM, WITH TWO 2.4G RP SMA Plugs (3dB)
2014-000022-A.0	Cellular, two antennas supporting IPX/MHF (Female) to SMA ST Jack (Male), 300 mm, two LTE 704-960/1710-2690MHz SMA ST Plug 2(dB) 50 Ω 161 mm

Eagle Eyes - AIML


6th Generation Intel® Core™ U Series Processor Fanless Box Computer, 2x RJ45 GbE

I/O Interface



Dimensions

units: mm



Order Information

Part Number

AIML6-6100-8G-2.5S128G-P209B12 Intel® 6th Gen Skylake U (SKL-U) platform, Core™ i3-6100U CPU, 2x DP, 1a VGA, 4 USB3.0, 1x RS 232/422/485, 3x RS-232, 2x GbE (RJ45), 16x GPIO (DIO), (no PoE+ or LAN expansion option), 8GB RAM, 128GB 2.5" SATA SSD, 90W Power Adapter & Cord.

Packing List

1. Eagle Eyes – AIML Embedded Box PC x 1
2. AC-DC Power Adapter (24V/160W) with pitch 5.0mm 3-pin terminal block plug
3. AC-DC Power Cord YP-12/YC-12, plug type B, American (USA)
4. Four rubber anti-slide pads with four (4) M2.5x5 screws